

CATALOG 2021



宁波上鑫脚轮有限公司

Ningbo Shangxin Caster Wheels Co.,Ltd.

地址：浙江宁波余姚市朗霞街道锦盛路187号
Address: No. 187, Jingsheng road, Langxia street,
Yuyao, Ningbo City, Zhejiang Province.
电话 / Tel: 86-0574-62188162
传真 / Fax: 86-0574-62190682
邮箱 / E-mail: sales@shangxincaster.com
网站 / Web: www.shangxincaster.com

**A GOOD CASTER CHOOSES
THE RAIN OF SAFETY**



Certificates



Company Introduce

Ningbo Shangxin Caster Wheels Co.,Ltd. is a enterprise who focus on R&D, manufacturing of caster, the company is fully occupied by professional engineers and well experienced operating stuffs. The products are mainly used in the fields of instrument, equipment, medical care, household, transportation, architecture and manufacturing. With cost effective and good quality products produced by advanced workmanship and technics, we received very good comment from customers all over the world. We also built strong R&D team in order to meet the special requirement for customers.

In order to strength the quality control, we built complete quality management system, equipped full range of testing equipment, so that any single piece can pass the life, salt-spray, impact strength testing. We guarantee every procedure is under strict supervision.

Caster is a small hardware sparepart, but it means all to us. As a leading manufacturer of caster, our final goal is to challenge ourselves, pursuit for perfect, every piece of caster is beyond the expectation of customer.

Production workshop



Warehouse



Warehouse



Molds



Molds



Testing Equipment



Testing Equipment



Testing Equipment



Production Machines



Production Machines



Production Machines



Production Machines



Production Machines



Test report



ROHS



ROHS



REACH205 COMPLIANT

Air cargo casters Test Report

Test Items: Impact & Endurance Test; Shore Hardness of Wheel; Impact Test (vertical/ horizontal); Dimensional Test

Impact Test

The impact test consisted of mounting the test caster by its normal attachment such that the caster will be struck on the wheel surface. The unit was released from a height to generate an impact force equal to the rated load (500 IN.LBS). Re-Test again at 700 IN LBS and also 900 IN LBS. Provide results of each test.

Model Number: CP24-AC-3 (CP24-AC-4)

Test condition: the same to above testing requirements by impact force 500lbs, 700lbs and 900lbs.

Pictures:



No.	SPEC.	Parameters		Acceptance Criteria	Notes
		Test Description	Test Value		
1	Impact Test	Each wheel load capacity 1	237.263kgs(>500lbs)	The test is passed without deformation of the sample, with normal rotating effects	
		Each wheel load capacity 2	322.547kgs(>700lbs)	The test is passed without deformation of the sample, with normal rotating effects	
		Each wheel load capacity 3	422.141kgs(>700lbs)	The test is passed without deformation of the sample, with normal rotating effects	

Endurance Test

The endurance test consisted of mounting the test caster to the load arm of our drum type test machine. 500 LBS was applied on the caster, with a surface speed of 2.0 mph using a test surface of smooth steel with a 1/8X2" bump. The machine was set at intermittent travel time (2 minutes on 2 minutes off) to prevent excessive axle heat build up. The wheel was run for 4 miles.

Model Number: CP24-AC-3(CP24-AC-4)

Test condition: The durability test consists of mounting the test caster onto the load arm of the drum type testing machine. A load of 185kg was applied to the caster, and the surface speed was 3.3km/h. The test surface was made of smooth steel with two bumps of 2mm thickness. After driving for 1.3km, the bumps were removed and the test was continued. The machine is set to run intermittently for 3 minutes, stop for 1 minute and retrograde for 3 minutes. The wheel actually ran 2.9 kilometers.

Pictures: (shangxin caster samples test)



No.	SPEC.	Parameters		Acceptance Criteria	Notes
		Test Description	Test Value		
1	Endurance Test	Test Load	227kgs load capacity value (=500lbs)	The test is passed without deformation of the sample, with normal rotating effects	
		Average Speed on smooth steel	3.3 km/h (>2.0 mph =3.22km/h)	The test is passed without deformation of the sample, with normal rotating effects	
		Total Actual mechanical travel	2.9km (1.81 miles <4 miles value)	The test is passed without deformation of the sample, with normal rotating effects	
		Pause and start Time interval	Pause: 1 min ; Start: 3 mins (start time is above 2 mins)	The test is passed without deformation of the sample, with normal rotating effects	

Wheel Hardness Test

Hardness is 71D.

Pictures:



Model Number: CP24-AC-4

Test condition: 70.5D


Dimensional Test

AIR CARGO CASTER (CP24-AC-4)

Part Number: ACPSF-27-137-PP3 B&N PA TG YZ ORANGE WHL NEW BEARING		
Model number:CP24-AC-4	Wheel Material: Polypropylene	Plate Dimensions: 4-7/16"
Load Rating: 400 LBS 180kgs	Wheel Bearing: Precision Ball Bearing (2)	Bolt Hole Pattern: 3-9/16"
Swivel Bearing: Precision Ball Bearing	Wheel Diameter: 2-3/4"	Overall Height: 4-1/32"
Finish: Yellow ZC Dichromate Horn	Wheel Width: 1-3/8"	

Model Number: CP24-AC-3 (CP24-AC-4)

Test condition: See attached pictures(all data is seriously tested and the same to the blueprint)



Pictures:



Catalog



P01-29
Light Medium Duty Casters



P76-78
PP Wheels



P30-51
Heavy Duty Casters



P79-80
Phenolic Wheels



P52-58
Special Applied Casters



P81-85
Fork Lift Truck Wheels



P59-66
PU Wheels



P86-90
Hand Trolleys



P67-69
Rubber Wheels



P91
Floor Locks



P70-71
Nylon Wheels



P92-99
Medium Heavy Duty Forks



P72-75
Cast Iron Wheels



P100-116
Leveling Feet



Model No.: CP1

Product name: Light Duty Nylon Casters

Optional Wheel: Nylon wheel/PP wheel/TPR wheel

Loading capacity: 38~70KGS

Housing: Made of pressed steel, zinc plated, double ballrace swivel head Stainless steel housing is available

Wheel Material: Nylon

Bearing Type: Plain Bearing

Temperature range: -15°C~80°C



Swivel Caster	Model	Wheel Size (mm)							Load Capacity (kg)
		50*19	60*23	80*24	100*24	60*60*2	46*46	12*6	
	CP1S-NW50.19	50*19	72	20	60*60*2	46*46	12*6	23*2	38
	CP1S-NW60.23	60*23	82	22	60*60*2	46*46	12*6	30*2	50
	CP1S-NW80.24	80*24	104	28	60*60*2	46*46	12*6	31*2	60
	CP1S-NW100*24	100*24	121	30	60*60*2	46*46	12*6	31*2	70

Rigid Caster	Model	Wheel Size (mm)							Load Capacity (kg)
		50*19	60*23	80*24	100*24	60*60*2	46*46	12*6	
	CP1R-NW50.19	50*19	72	/	60*60*2	46*46	12*6	23*2	38
	CP1R-NW60.23	60*23	82	/	60*60*2	46*46	12*6	30*2	50
	CP1R-NW80.24	80*24	104	/	60*60*2	46*46	12*6	31*2	60
	CP1R-NW100*24	100*24	121	/	60*60*2	46*46	12*6	31*2	70

Double Brake Caster	Model	Wheel Size (mm)							Load Capacity (kg)
		50*19	60*23	80*24	100*24	60*60*2	46*46	12*6	
	CP1T-NW50.19	50*19	72	20	60*60*2	46*46	12*6	23*2	38
	CP1T-NW60.23	60*23	82	22	60*60*2	46*46	12*6	30*2	50
	CP1T-NW80.24	80*24	104	28	60*60*2	46*46	12*6	31*2	60
	CP1T-NW100*24	100*24	121	30	60*60*2	46*46	12*6	31*2	70

Bolt Hole Swivel Caster	Model	Wheel Size (mm)							Load Capacity (kg)
		50*19	60*23	80*24	100*24	60*60*2	46*46	12*6	
	CP1HS-NW50.19	50*19	72	20	10.3	Plain bore	23*2	38	
	CP1HS-NW60.23	60*23	82	22	10.3	Plain bore	30*2	50	
	CP1HS-NW80.24	80*24	104	28	10.3	Plain bore	31*2	60	
	CP1HS-NW100*24	100*24	121	30	10.3	Plain bore	31*2	70	

Bolt Hole Double Brake Caster	Model	Wheel Size (mm)							Load Capacity (kg)
		50*19	60*23	80*24	100*24	60*60*2	46*46	12*6	
	CP1HT-NW50.19	50*19	72	20	10.3	Plain bore	23*2	38	
	CP1HT-NW60.23	60*23	82	22	10.3	Plain bore	30*2	50	
	CP1HT-NW80.24	80*24	104	28	10.3	Plain bore	31*2	60	
	CP1HT-NW100*24	100*24	121	30	10.3	Plain bore	31*2	70	

Optional Wheels



Features & Advantages:

1. Dust proof for seal with stainless steel housing available
2. Standard design for different wheels optional such as TPR, Nylon & Plastic Wheels
3. 20 years of industry experience technician processing technology

Specification:

Type: Light Duty Nylon Casters	Surface Treatment: Zinc Plated
Wheel size(mm): 50*19~100*24	Tread Color: White
Tread Material: Nylon	Applicable Temperature: -15°C~80°C
Mounting Height(mm): 72 / 82 / 104 / 121	Load Capacity(kgs): 38~70
Plate Thickness(mm): 2	Bearing Type: Plain bearings

Model No.: CP2

Product name: Transparent PU Casters

Optional Wheel: Nylon wheel/PP wheel/TPR wheel

Loading capacity: 25~50KGS

Housing: Made of pressed steel, zinc plated and Chrome plated optional, double ballrace swivel head Stainless steel housing is available

Wheel Material: Nylon

Bearing Type: Plain Bearing

Temperature range: -40°C~80°C



	Model								
 CP2S1	CP2S1-PCPU35.24 CP2S2-PCPU35.24	35*24	50.5	16.5	42*42*2	32*32	4.5	23*2	25
	CP2S1-PCPU50.21 CP2S2-PCPU50.21	50*21	64	18.5	42*42*2	32*32	4.5	30*2	35
 CP2S2	CP2S1-PCPU75.23 CP2S2-PCPU75.23	75*23	98	28	60*60*2	45*45	8.5*6.5	31*2	40
	CP2S1-PCPU100.24 CP2S2-PCPU100.24	100*24	124	30.5	60*60*2	45*45	8.5*6.5	31*2	50

	Model								
 CP2T1	CP2T1-PCPU35.24 CP2T2-PCPU35.24	35*24	50.5	16.5	42*42*2	32*32	4.5	23*2	25
	CP2T1-PCPU50.21 CP2T2-PCPU50.21	50*21	64	18.5	42*42*2	32*32	4.5	30*2	35
 CP2T2	CP2T1-PCPU75.23 CP2T2-PCPU75.23	75*23	98	28	60*60*2	45*45	8.5*6.5	31*2	40
	CP2T1-PCPU100.24 CP2T2-PCPU100.24	100*24	124	30.5	60*60*2	45*45	8.5*6.5	31*2	50

	Model								
 CP2SS2 Threaded Stem Swivel Caster	CP2SS2-PCPU35.24	35*24	50.5	16.5	Plain Bore	8*15 / 8*25	23*2	38	
	CP2SS2-PCPU50.21	50*21	64	18.5	Plain Bore	10*15 / 10*25	30*2	50	
	CP2SS2-PCPU75.23	75*23	98	28	Plain Bore	12*25	31*2	60	
	CP2SS2-PCPU100.24	100*24	124	30.5	Plain Bore	12*25	31*2	70	

Optional Wheels



Features & Advantages:

1. Agility, easy moving and durability
2. 20 years of industry experience technician processing technology

Specification:

Type: Transparent PU Casters	Surface Treatment: Zinc Plated or chromate plated
Wheel size(mm): 35*24~100*24	Tread Color: Transparent
Tread Material: PC+PU	Applicable Temperature: -40°C~80°C
Mounting Height(mm): 50.5 / 64 / 98 / 124	Load Capacity(kgs): 25~50
Plate Thickness(mm): 2	Bearing Type: Plain bearings

Model No.: CP3
 Product name: Twin Wheel Casters for Furniture
 Optional Wheel: Nylon wheel/PP wheel/TPR wheel
 Loading capacity: 60-80KGS
 Housing: Made of pressed steel, zinc plated and Chrome plated
 Wheel Material: Nylon/rubber/plastic
 Bearing Type: Plain Bearing
 Temperature range: -40°C-80°C



	Model							
	Swivel Caster	CP3S-TW-PP60.24	60*24	73	71*51	51*35	8*10.5	60*1.5
	CP3S-TW-PP75.24	75*24	102	92.6*63.2	73*45	8.2*11.2	60*1.5	80

	Model							
	Swivel with Total Brake Caster	CP3T-TW-PP60.24	60*24	73	71*51	51*35	8*10.5	60*1.5
	CP3T-TW-PP75.24	75*24	102	92.6*63.2	73*45	8.2*11.2	60*1.5	80

	Model							
	Rigid Caster	CP3R-TW-TPR60.24	60*24	73	71*51	51*35	8*10.5	60*1.5
	CP3R-TW-TPR75.24	75*24	102	92.6*63.2	73*45	8.2*11.2	60*1.5	80

	Model					
	Bolt Hole Swivel Caster	CP3HS-TW-TPR60.24	60*24	73	M12	60*1.5
	CP3HS-TW-TPR75.24	75*24	102	M12	60*1.5	80

	Model					
	Bolt Hole Swivel with Total Brake Caster	CP3HT-TW-TPR60.24	60*24	73	M12	60*1.5
	CP3HT-TW-TPR75.24	75*24	102	M12	60*1.5	80

Optional Wheels



Features & Advantages:

1. Exquisite craftsmanship and excellent quality, support to customize special models
2. Optional hole top type, different connection ways, to meet various needs
3. Wheel brake, directional brake, one key in place, stable parking, good fixity
4. Elastic rubber edge double wheel, noise elimination, shock absorption and wear resistance, road bumps still running smoothly, anti-skid and mute, no wheel mark
5. Select high quality steel with fine quality, uniform color, strong surface adhesion and corrosion resistance

Specification:

Type: Twin Wheel Casters for Furniture	Surface Treatment: Zinc Plated
Wheel size(mm): 60*24/75*24	Tread Color: Black
Tread Material: Nylon/rubber/plastic	Applicable Temperature: -40°C-80°C
Mounting Height(mm): 73/102	Load Capacity(kgs): 60/80
Plate Thickness(mm): 2	Bearing Type: Plain bearings

Model No.: CP4
 Product name: Medium Duty TPR Casters
 Optional Wheel: Black PP wheel, white nylon wheel and TPR Wheel
 Loading capacity: 80-130KGS
 Housing: Made of pressed steel, zinc plated, double ball race swivel head
 Material: TPR
 Bearing Type: Double ball Bearing
 Temperature range: -15°C-60°C



	Model							
	CP4S-TPR75.32	75*32	105	95*66	73*45	8	23*2	80
	CP4S-TPR100.32	100*32	130	95*66	73*45	8	30*2	100
	CP4S-TPR125.32	125*32	154	95*66	73*45	8	31*2	130

	Model							
	CP4R-TPR75.32	75*32	105	95*66	73*45	8	23*2	80
	CP4R-TPR100.32	100*32	130	95*66	73*45	8	30*2	100
	CP4R-TPR125.32	125*32	154	95*66	73*45	8	31*2	130

	Model							
	CP4T-TPR75.32	75*32	105	95*66	73*45	8	23*2	80
	CP4T-TPR100.32	100*32	130	95*66	73*45	8	30*2	100
	CP4T-TPR125.32	125*32	154	95*66	73*45	8	31*2	130

	Model						
	CP4SS-TPR75.32	75*32	105	M12*30	Double ball	23*2	80
	CP4SS-TPR100.32	100*32	130	M12*30	Double ball	30*2	100
	CP4SS-TPR125.32	125*32	154	M12*30	Double ball	31*2	130

	Model						
	CP4ST-TPR75.32	75*32	105	M12*30	Double ball	23*2	80
	CP4ST-TPR100.32	100*32	130	M12*30	Double ball	30*2	100
	CP4ST-TPR125.32	125*32	154	M12*30	Double ball	31*2	130

Optional Wheels



Features & Advantages:

1. High quality super thermoplastic rubber, environmental friendly material, quiet and wear-resistant, leaving no trace
2. The top and bottom glass plates are equipped with high-quality steel balls and high-quality lubricating grease to make the steering silky smooth, labor-saving and long service life
3. 6001 bearing steel, high hardness, high limit speed, large bearing pressure, small rotating noise, double bearings, more stable and long service life
4. The support is made of one-piece stamping, which has high strength and good stability. Environmental protection galvanized treatment, through salt spray test up to level 6 standard, more corrosion resistance
5. Hrc50-55 steel ball, high hardness, even texture, smooth surface, smooth rotation and wear resistance
6. High quality hex anti-skid nut, strong and durable, not easy to fall off, not slippery

Specification:

Type: Medium Duty TPR Casters	Surface Treatment: Zinc Plated
Wheel size(mm): 75*32 / 100*32 / 125*32	Tread Color: Gray
Tread Material: TPR	Applicable Temperature: -15°C-60°C
Mounting Height(mm): 105 / 130 / 154	Load Capacity(kgs): 80-130
Plate Thickness(mm): 2.5	Bearing Type: Double ball bearings

Model No.: CP5
 Product name: PU on PP Stainless Steel Casters
 Optional Wheel: Black PP wheel, white nylon wheel and TPR Wheel
 Loading capacity: 70-120KGS
 Housing: Made of pressed steel, zinc plated, double ballrace swivel head
 Material: pu on pp
 Bearing Type: Double ball Bearing
 Temperature range: -30°C-80°C



	Model							
	CP5S-PPS80.30	80*30	106	37.5	105*82.5*3	80*60	9	70
	CP5S-PPS100.30	100*30	128	40	105*82.5*3	80*60	9	100
	CP5S-PPS125.35	125*35	155	47	105*82.5*3	80*60	9	120

	Model							
	CP5R-PPS80.30	80*30	106	/	105*82.5*3	80*60	9	70
	CP5R-PPS100.30	100*30	128	/	105*82.5*3	80*60	9	100
	CP5R-PPS125.35	125*35	155	/	105*82.5*3	80*60	9	120

	Model							
	CP5T-PPS80.30	80*30	106	37.5	105*82.5*3	80*60	9	70
	CP5T-PPS100.30	100*30	128	40	105*82.5*3	80*60	9	100
	CP5T-PPS125.35	125*35	155	47	105*82.5*3	80*60	9	120

Optional Wheels



Features & Advantages:

1. Carbon steel high hardness double bearing, heavy load, easy and flexible driving
2. High tech PU polyurethane design, promoting labor saving, environmental protection and no peculiar smell
3. High quality stainless steel bracket, bright color, waterproof, rust proof and corrosion proof
4. Special high quality hard steel ball, flexible and smooth, with butter inside, durable

Specification:

Type: PU on PP Stainless Steel Casters	Surface Treatment: Stainless steel
Wheel size(mm): 80*30 / 100*30 / 125*35	Tread Color: Gray
Tread Material: PU	Applicable Temperature: -30°C-80°C
Mounting Height(mm): 106 / 128 / 155	Load Capacity(kgs): 70-120
Plate Thickness(mm): 3	Bearing Type: Double ball bearings



Light Medium Duty Casters

Model No.: CP6
 Product name: PU on PP Shopping Cart Casters
 Optional Wheel: Black PP wheel, white nylon wheel and TPR Wheel
 Loading capacity: 80~100KGS
 Housing: Made of pressed steel, zinc plated, single ballrace swivel head
 Material: pu on pp
 Bearing Type: Double ball bearing
 Temperature range: -30°C~80°C



		Model					
 CP6SS-1 Threaded Stem Swivel		CP6SS-S100.25	100*25	154	33*2.5	M12*18 / *30	80
		CP6SS-S125.32	125*32	179	40*2.5	M12*18 / *30	100

Optional Wheels



Features & Advantages:

1. It is not easy to deform, full of steel balls, sufficient grease, small bracket clearance, double ball disc, and can rotate freely
2. Surface treatment: 304 stainless steel plate, mirror polishing, oil proof, rust proof and waterproof
3. Select high quality bearing, flexible and labor-saving rotation

Specification:

Type: PU on PP Shopping Cart Casters	Surface Treatment: Zinc plated
Wheel size(mm): 100*25 / 125*32	Tread Color: Black
Tread Material: PU	Applicable Temperature: -30°C~80°C
Mounting Height(mm): 154 / 179	Load Capacity(kgs): 80~100
Plate Thickness(mm): 2.5	Bearing Type: Double ball bearings



Model No.: CP7
 Product name: Medical Casters
 Optional Wheel: NA
 Loading capacity: 60~110KGS
 Housing: housing PA-G33 material with steel plate
 Wheel Material: PP core with TPR tread
 Bearing Type: Ball Bearings
 Temperature range: -40°C~80°C



		Model							
 Swivel Caster		CP7P-MTC-JPS75-1	76*58	103	65	70*57	50*40-60*45	12*20	Ball Bearings 60
		CP7P-MTC-JPS75-2	76*58	103	65	96*64	60*50-70*55	12*20	Ball Bearings 60
		CP7P-MTC-JPS100-1	100*70	125	73	70*57	50*40-60*45	12*20	Ball Bearings 80
		CP7P-MTC-JPS100-2	100*70	125	73	96*64	60*50-70*55	12*20	Ball Bearings 80
		CP7P-MTC-JPS125	125*80	155	85	96*64	60*50-70*55	12*20	Ball Bearings 110

		Model							
 Brake with Swivel		CP7P-MTC-JPB75-1	76*58	103	65	70*57	50*40-60*45	12*20	Ball Bearings 60
		CP7P-MTC-JPB75-2	76*58	103	65	96*64	60*50-70*55	12*20	Ball Bearings 60
		CP7P-MTC-JPB100-1	100*70	125	73	70*57	50*40-60*45	12*20	Ball Bearings 80
		CP7P-MTC-JPB100-2	100*70	125	73	96*64	60*50-70*55	12*20	Ball Bearings 80
		CP7P-MTC-JPB125	125*80	155	85	96*64	60*50-70*55	12*20	Ball Bearings 110

	Model							
	CP7P-MTC-JTS75	76*58	94	65	Threaded stem	M12*25	Ball Bearings	60
	CP7P-MTC-JTS100	100*70	125	73	Threaded stem	M12*25	Ball Bearings	80
	CP7P-MTC-JTS125	125*80	145	85	Threaded stem	M12*25	Ball Bearings	110

	Model							
	CP7P-MTC-JTB75	76*58	94	65	Threaded stem	M12*25	Ball Bearings	60
	CP7P-MTC-JTB100	100*70	125	73	Threaded stem	M12*25	Ball Bearings	80
	CP7P-MTC-JTB125	125*80	145	85	Threaded stem	M12*25	Ball Bearings	110

Features & Advantages:

Quiet wear-resistant, light operation, flexible steering, large elasticity, special super quiet bearing, anti winding.

Specification:

Type: Medical Casters	Surface Treatment: Zinc plated
Wheel size(mm): 76*58-125*80	Tread Color: Gray and white
Tread Material: TPR	Applicable Temperature: -40°C~80°C
Mounting Height(mm): 103-155	Load Capacity(kgs): 60-110
Plate Thickness(mm): 2	Bearing Type: Ball bearings

Medical Caster MEC Series (Round rim)



3 inch	76	32	90	6202	TPR
4 inch	101	32	120	6202	TPR
5 inch	126	32	135	6202	TPR



CP7C-MEC-JPS76.32
CP7C-MEC-JPS101.32
CP7C-MEC-JPS126.32



CP7C-MEC-JPB76.32
CP7C-MEC-JPB101.32
CP7C-MEC-JPB126.32



CP7C-MEC-JTS76.32
CP7C-MEC-JTS101.32
CP7C-MEC-JTS126.32



CP7C-MEC-JTB76.32
CP7C-MEC-JTB101.32
CP7C-MEC-JTB126.32



CP7C-MEC-JHS76.32
CP7C-MEC-JHS101.32
CP7C-MEC-JHS126.32



CP7C-MEC-JHS76.32
CP7C-MEC-JHS101.32
CP7C-MEC-JHS126.32



CP7C-MEC-JRS76.32
CP7C-MEC-JRS101.32
CP7C-MEC-JRS126.32



CP7C-MEC-JRS76.32
CP7C-MEC-JRS101.32
CP7C-MEC-JRS126.32

Medical Caster MEC Series (Flat rim)



3 inch	76	32	90	6202	TPR	
4 inch	101	32	120	6202	TPR	
5 inch	126	32	135	6202	TPR	



CP7P-MEC-JPS76.32
CP7P-MEC-JPS101.32
CP7P-MEC-JPS126.32



CP7P-MEC-JPB76.32
CP7P-MEC-JPB101.32
CP7P-MEC-JPB126.32



CP7P-MEC-JTS76.32
CP7P-MEC-JTS101.32
CP7P-MEC-JTS126.32



CP7P-MEC-JTB76.32
CP7P-MEC-JTB101.32
CP7P-MEC-JTB126.32



CP7P-MEC-JHS76.32
CP7P-MEC-JHS101.32
CP7P-MEC-JHS126.32



CP7P-MEC-JHS76.32
CP7P-MEC-JHS101.32
CP7P-MEC-JHS126.32



CP7P-MEC-JRS76.32
CP7P-MEC-JRS101.32
CP7P-MEC-JRS126.32



CP7P-MEC-JRS76.32
CP7P-MEC-JRS101.32
CP7P-MEC-JRS126.32

Medical Caster MTC Series



CP7P-MTC-JPS75.58



CP7P-MTC-JPB75.58



CP7P-MTC-JPS100.70



CP7P-MTC-JPB100.70



CP7P-MTC-JPS125.80



CP7P-MTC-JPB125.80

Fitting Dimension

3 inch	105.5	60.5	2.5	Injection molding	75	58	60	Ball bearings	PA+PU	
4 inch	138.5	79.5	2.5	Injection molding	100	70	80	6001	PA+PU	
5 inch	160	101.5	2.5	Injection molding	125	80	100	6202	PA+PU	

Medicar Caster MTC Series



CP7P-MTC-JTS75.58



CP7P-MTC-JTB75.58



CP7P-MTC-JTS100.70



CP7P-MTC-JTB100.70



CP7P-MTC-JTS125.80



CP7P-MTC-JTB125.80

Fitting Dimension

3 inch	94.5	60.5	Injection molding	75	58	60	Ball bearings	PA+PU
4 inch	127.5	79.5	Injection molding	100	70	80	6001	PA+PU
5 inch	149	101.5	Injection molding	125	80	100	6202	PA+PU

Medical Caster Normal Series



CP7P-STU-CBS75.32
CP7P-STU-CBS10032
CP7P-STU-CBS125.32



CP7P-STU-CBS75.32
CP7P-STU-CBS10032
CP7P-STU-CBS125.32

Fitting Dimension

3 inch	118	65	2	Injection molding	75	32	70	6202	PU/TPR
4 inch	130	84	2	Injection molding	100	32	90	6202	PU/TPR
5 inch	128	105	2.5	Injection molding	126	32	145	6202	PU/TPR

Medical Caster Ladle Cover Series



CP7C-STC-JTB126.32



CP7C-STC-JTS126.32

Fitting Dimension

5 inch	128	105	2.5	Injection molding	126	32	145	6202	PU.TPR

Stainless Steel Light Series PU caster

1.5 inch	40	20	30	6000	PU
2 inch	50	22	50	6000	PU



CP7C-SPU-SPS40.20
CP7C-SPU-SPS50.22



CP7C-SPU-SPB40.20
CP7C-SPU-SPB50.22



CP7C-SPU-SPR40.20
CP7C-SPU-SPR50.22

Stainless Steel Light Series PA caster

1.5 inch	40	20	30	6000	PA
2 inch	50	22	50	6000	PA



CP7C-SPA-SPS40.20
CP7C-SPA-SPS50.22



CP7C-SPA-SPB40.20
CP7C-SPA-SPB50.22



CP7C-SPA-SPR40.20
CP7C-SPA-SPR50.22



Light Medium Duty Casters

Stainless Steel Light Series TPR caster

					
1.5 inch	40	20	30	6000	TPR
2 inch	50	22	50	6000	TPR



CP7C-SCT-SPS40.20
CP7C-SCT-SPS50.22









CP7C-SCT-SPB40.20
CP7C-SCT-SPB50.22



CP7C-SCT-SPR40.20
CP7C-SCT-SPR50.22

Stainless Steel Light Series TPR conductive caster

					
1.5 inch	40	20	30	6000	TPR + Conductive wire
2 inch	50	22	50	6000	TPR + Conductive wire



CP7C-SDD-SPS40.20
CP7C-SDD-SPS50.22



CP7C-SDD-SPB40.20
CP7C-SDD-SPB50.22



CP7C-SDD-SPR40.20
CP7C-SDD-SPR50.22



Model No.: CP8

Product name: Light Duty PU on PP Casters

Optional Wheel: Black PP wheel, white nylon wheel and TPR Wheel

Loading capacity: 40-60KGS



Housing: Made of pressed steel, zinc plated, double ballrace swivel head








Material: pu on pp







Bearing Type: Double ball Bearing

Temperature range: -30°C-80°C



	Model						
Swivel Caster	CP8P-PUP-SPS38.20	38*20	60	19	54*44*2	40 / 30*40 / 30	6.2 40
	CP8P-PUP-SPS50.20	50*20	70	20	54*44*2	40 / 30*40 / 30	6.2 50
	CP8P-PUP-SPS63.20	63*20	85	20	54*44*2	40 / 30*40 / 30	6.2 60

	Model						
Rigid Caster	CP8P-PUP-SPR38.20	38*20	60	/	54*44*2	40 / 30*40 / 30	6.2 40
	CP8P-PUP-SPR50.20	50*20	70	/	54*44*2	40 / 30*40 / 30	6.2 50
	CP8P-PUP-SPR63.20	63*20	85	/	54*44*2	40 / 30*40 / 30	6.2 60

	Model						
Double Brake Caster	CP8P-PUP-SPB38.20	38*20	60	19	54*44*2	40 / 30*40 / 30	6.2 40
	CP8P-PUP-SPB50.20	50*20	70	20	54*44*2	40 / 30*40 / 30	6.2 50
	CP8P-PUP-SPB63.20	63*20	85	20	54*44*2	40 / 30*40 / 30	6.2 60



Optional Wheels



Features & Advantages:

1. 20%Thickened base, thickened floor, strong bearing capacity, more stable installation, 20% higher load than similar products
2. Good brake performance, reasonable design structure, wear resistance, no slip at all
3. Thickened bearing rivets, solid bearing rivets, galvanized treatment, extended caster service life
4. Pu and PP materials are preferred, which are firm and wear-resistant without degumming
5. Focus on details, beautiful appearance, no processing defects, well received by customers

Specification:

Type: Light Duty PU on PP Casters	Surface Treatment: Zinc plated
Wheel size(mm): 38*20 / 50*20 / 63*20	Tread Color: Gray and blue
Tread Material: PU	Applicable Temperature: -30°C~80°C
Mounting Height(mm): 60 / 70 / 85	Load Capacity(kgs): 40-60
Plate Thickness(mm): 2	Bearing Type: Ball bearings



Model No.: CP9
 Product name: Light Medium Duty PU on PP Casters
 Optional Wheel: Black PP wheel, white nylon wheel and TPR Wheel
 Loading capacity: 70-90KGS
 Housing: Made of pressed steel, zinc plated, double ballrace swivel head
 Material: pu on pp
 Bearing Type: Single ball Bearing
 Temperature range: -30°C-80°C



Swivel Caster	Model							
	CP9P-PUP-SPS63.25	63*25	91	34	70*58*2.5	55.5 / 54.5*44.2 / 37.2	8.2	70
CP9P-PUP-SPS75.25	75*25	104	30	70*58*2.5	55.5 / 54.5*44.2 / 37.2	8.2	80	
CP9P-PUP-SPS100.25	100*25	126	25	70*58*2.5	55.5 / 54.5*44.2 / 37.2	8.2	90	

Rigid Caster	Model							
	CP9P-PUP-SPR63.25	63*25	91	/	70*58*2	55.5 / 54.5*44.2 / 37.2	8.2	70
CP9P-PUP-SPR75.25	75*25	104	/	70*58*2	55.5 / 54.5*44.2 / 37.2	8.2	80	
CP9P-PUP-SPR100.25	100*25	126	/	70*58*2	55.5 / 54.5*44.2 / 37.2	8.2	90	

Double Brake Caster	Model							
	CP9P-PUP-SPB63.25	63*25	91	34	70*58*2.5	55.5 / 54.5*44.2 / 37.2	8.2	70
CP9P-PUP-SPB75.25	75*25	104	30	70*58*2.5	55.5 / 54.5*44.2 / 37.2	8.2	80	
CP9P-PUP-SPB100.25	100*25	126	25	70*58*2.5	55.5 / 54.5*44.2 / 37.2	8.2	90	

Bolt Hole Swivel	Model						
	CP9P-PUP-JHS63.25	63*25	87	34	10.2	70	
CP9P-PUP-JHS75.25	75*25	101	30	10.2	80		
CP9P-PUP-JHS100.25	100*25	122	23	10.2	90		



Light Medium Duty Casters

 Bolt Hole Swivel with Brake	Model					
	CP9P-PUP-JHB63.25	63*25	87	34	10.2	70
	CP9P-PUP-JHB75.25	75*25	101	30	10.2	80
	CP9P-PUP-JHB100.25	100*25	122	23	10.2	90

Optional Wheels



Plastic Wheel



Nylon Wheel



TPR Wheel

Features & Advantages:

1. The wheels are made of pure PU material, which is quiet and wear-resistant, more stable and reduces the operation intensity of users
2. The bearing adopts high-quality ball, with quality guarantee, flexible and fast operation, quiet and comfortable, and enhanced bearing capacity
3. The 2.5mm steel base plate is adopted, with strong load and gravity, which is firm and also increases the load strength
4. Various types of wheels, complete styles, wider selection and application, can provide customized development for customers

Specification:

Type: Light Medium Duty PU on PP Casters	Surface Treatment: Zinc plated
Wheel size(mm): 63*25 / 75*25 / 100*25	Tread Color: Gray and blue
Tread Material: PU	Applicable Temperature: -30°C~80°C
Mounting Height(mm): 91 / 104 / 126	Load Capacity(kgs): 70~90
Plate Thickness(mm): 2.5	Bearing Type: Ball bearings



Model No.: CP10

Product name: PU on PP Medium Duty Casters

Optional Wheel: Black PP wheel, white nylon wheel and TPR Wheel

Loading capacity: 120~180KGS









Housing: Made of pressed steel, zinc plated, double ballrace swivel head









Material: pu on pp









Bearing Type: Double ball Bearing

Temperature range: -30°C~80°C



 Swivel Caster	Model							
	CP10P-PUP-SPS75.32	75*32	108	40	95*64*4	71 / 78*45	8.5	120
	CP10P-PUP-SPS100.32	100*32	133	36	95*64*4	71 / 78*45	8.5	170
	CP10P-PUP-SPS125.32	125*32	160	36	95*64*4	71 / 78*45	8.5	180

 Rigid Caster	Model							
	CP10P-PUP-SPR75.32	75*32	108	/	95*64*3	71 / 78*45	8.5	120
	CP10P-PUP-SPR100.32	100*32	133	/	95*64*3	71 / 78*45	8.5	170
	CP10P-PUP-SPR125.32	125*32	160	/	95*64*3	71 / 78*45	8.5	180

 Double Brake Caster	Model							
	CP10P-PUP-SPB75.32	75*32	108	40	95*64*4	71 / 78*45	8.5	120
	CP10P-PUP-SPB100.32	100*32	133	36	95*64*4	71 / 78*45	8.5	170
	CP10P-PUP-SPB125.32	125*32	160	36	95*64*4	71 / 78*45	8.5	180



Optional Wheels



Features & Advantages:

- 1. The adhesion between Pu and cast iron core is very strong, which improves the product life grade
- 2. International grade ball bearing, lubrication and wear resistance, flexible rotation
- 3. 20 years advanced and mature manufacturing process engineer

Specification:

Type: PU on PP Medium Duty Casters	Surface Treatment: Zinc plated
Wheel size(mm): 75*32 / 100*32 / 125*32	Tread Color: Gray and blue
Tread Material: PU	Applicable Temperature: -30°C~80°C
Mounting Height(mm): 108 / 133 / 160	Load Capacity(kgs): 120~180
Plate Thickness(mm): 4	Bearing Type: Ball bearings



Model No.: CP11
 Product name: PU on Iron Medium Duty Casters
 Optional Wheel: PU wheel, PP wheel, white nylon wheel and TPR Wheel
 Loading capacity: 100~140KGS
 Housing: Made of pressed steel, zinc plated, double ballrace swivel head
 Material: pu on pp
 Bearing Type: Double ball Bearing
 Temperature range: -30°C~80°C



	Model							
Swivel Caster	CP11S-PI75.32	75*32	102	33	94*63*3	73 / 44*3	8.5*11.5	100
	CP11S-PI100.32	100*32	128	35	94*63*3	73 / 44*3	8.5*11.5	130
	CP11S-PI125.32	125*32	157	37	94*63*3	73 / 44*3	8.5*11.5	140

	Model							
Rigid Caster	CP11R-PI75.32	75*32	102	NA	94*63*3	73 / 44*3	8.5*11.5	100
	CP11R-PI100.32	100*32	128	NA	94*63*3	73 / 44*3	8.5*11.5	130
	CP11R-PI125.32	125*32	157	NA	94*63*3	73 / 44*3	8.5*11.5	140

	Model							
Double Brake Caster	CP11T-PI75.32	75*32	102	33	94*63*3	73 / 44*3	8.5*11.5	100
	CP11T-PI100.32	100*32	128	35	94*63*3	73 / 44*3	8.5*11.5	130
	CP11T-PI125.32	125*32	157	37	94*63*3	73 / 44*3	8.5*11.5	140



Light Medium Duty Casters

Optional Wheels



Features & Advantages:

1. Castor environmental protection material anti-skid and wear-resistant
2. High quality material, fine artwork and smooth surface looking
3. Specific customization support

Specification:

Type: PU on Iron Medium Duty Casters	Surface Treatment: Zinc plated
Wheel size(mm): 75*32 / 100*32 / 125*32	Tread Color: Red
Tread Material: PU	Applicable Temperature: -30°C~80°C
Mounting Height(mm): 102 / 128 / 157	Load Capacity(kgs): 100~140
Plate Thickness(mm): 3	Bearing Type: Ball bearings

Heavy Duty Casters



Model No.: CP41

Product name: PU on Nylon Casters

Optional Wheel: PU on PP wheel, round tread PU on PP wheel, black rubber wheel, white nylon wheel, black rubber on pp wheel, rubber on nylon wheel

Loading capacity: 100~300KGS

Housing: made of pressed steel, zinc plated, double ballrace swivel head, dust proof seal

Wheel Material: PU on nylon

Bearing Type: Roller bearing / ball bearing / plain bearing

Temperature range: -35°C~90°C



	Model									
	CP41S-PN80.30	80*30	108	37	105*85*3	80*60	14*9	42*2.5	6202*2	100
	CP41S-PN100.30	100*30	128	37	105*85*3	80*60	14*9	42*2.5	6202*2	120
	CP41S-PN125.30	125*30	155	37	105*85*3	80*60	14*9	42*2.5	6202*2	150
	CP41S-PN125.40	125*40	156	42	135*110*4	105*80	16*11	52*2.5	6202*2	150
	CP41S-PN160.45	160*45	195	55	135*110*4	105*80	16*11	62*3	6203*2	250
	CP41S-PN200.50	200*50	240	55	135*110*4	105*80	16*11	62*3	6203*2	300

	Model									
	CP41R-PN80.30	80*30	108	/	105*85*3	80*60	14*9	42*2.5	6202*2	100
	CP41R-PN100.30	100*30	128	/	105*85*3	80*60	14*9	42*2.5	6202*2	120
	CP41R-PN125.30	125*30	155	/	105*85*3	80*60	14*9	42*2.5	6202*2	150
	CP41R-PN125.40	125*40	156	/	135*110*4	105*80	16*11	52*2.5	6202*2	150
	CP41R-PN160.45	160*45	195	/	135*110*4	105*80	16*11	62*3	6203*2	250
	CP41R-PN200.50	200*50	240	/	135*110*4	105*80	16*11	62*3	6203*2	300

	Model									
	CP41T-PN80.30	80*30	108	37	105*85*3	80*60	14*9	42*2.5	6202*2	100
CP41T-PN100.30	100*30	128	37	105*85*3	80*60	14*9	42*2.5	6202*2	120	
CP41T-PN125.30	125*30	155	37	105*85*3	80*60	14*9	42*2.5	6202*2	150	
CP41T-PN125.40	125*40	156	42	135*110*4	105*80	16*11	52*2.5	6202*2	150	
CP41T-PN160.45	160*45	195	55	135*110*4	105*80	16*11	62*3	6203*2	250	
CP41T-PN200.50	200*50	240	55	135*110*4	105*80	16*11	62*3	6203*2	300	

	Model							
	CP41SS-PN80.30	80*30	106	37	12*25	42*2.5	6202*2	100
CP41SS-PN100.30	100*30	126	37	12*25	42*2.5	6202*2	120	
CP41SS-PN125.30	125*30	153	37	12*25	42*2.5	6202*2	150	
CP41SS-PN125.40	125*40	153	42	12*25	52*2.5	6202*2	150	
CP41SS-PN160.45	160*45	191.5	55	16*40	62*3	6203*2	250	
CP41SS-PN200.50	200*50	236.5	55	16*40	62*3	6203*2	300	

	Model							
	CP41ST-PN80.30	80*30	106	37	12*25	42*2.5	6202*2	100
CP41ST-PN100.30	100*30	126	37	12*25	42*2.5	6202*2	120	
CP41ST-PN125.30	125*30	153	37	12*25	42*2.5	6202*2	150	
CP41ST-PN125.40	125*40	153	42	12*25	52*2.5	6202*2	150	
CP41ST-PN160.45	160*45	191.5	55	16*40	62*3	6203*2	250	
CP41ST-PN200.50	200*50	236.5	55	16*40	62*3	6203*2	300	

	Model							
	CP41HS-PN80.30	80*30	106	37	12.5	42*2.5	6202*2	100
CP41HS-PN100.30	100*30	126	37	12.5	42*2.5	6202*2	120	
CP41HS-PN125.30	125*30	153	37	12.5	42*2.5	6202*2	150	
CP41HS-PN125.40	125*40	153	42	12.5	52*2.5	6202*2	150	
CP41HS-PN160.45	160*45	191.5	55	16.5	62*3	6203*2	250	
CP41HS-PN200.50	200*50	236.5	55	16.5	62*3	6203*2	300	

	Model							
	CP41HT-PN80.30	80*30	106	37	12.5	42*2.5	6202*2	100
CP41HT-PN100.30	100*30	126	37	12.5	42*2.5	6202*2	120	
CP41HT-PN125.30	125*30	153	37	12.5	42*2.5	6202*2	150	
CP41HT-PN125.40	125*40	153	42	12.5	52*2.5	6202*2	150	
CP41HT-PN160.45	160*45	191.5	55	16.5	62*3	6203*2	250	
CP41HT-PN200.50	200*50	236.5	55	16.5	62*3	6203*2	300	

Optional Wheels



Features & Advantages:

1. Agility, easy moving and durability
2. Resistant to the chemical attack and radiation
3. Swivel bracket structure, dual track structure for more durable and reliable function.

Specification:

Type: PU on Nylon Casters	Surface Treatment: Zinc plated
Wheel size(mm): 80*30~200*50	Tread Color: Gray and blue
Tread Material: PU	Applicable Temperature: -35°C~90°C
Mounting Height(mm): 108~240	Load Capacity(kgs): 120~180
Plate Thickness(mm): 3 / 4	Bearing Type: Ball bearings

Model No.: CP42
 Product name: PU on PP Heavy Duty Casters
 Optional Wheel: PP wheel, nylon wheel, TPR Wheel, cast iron wheel
 Loading capacity: 400~500KGS
 Housing: Made of pressed steel, zinc plated, double ballrace swivel head
 Material: pu on pp
 Bearing Type: Double ball Bearing
 Temperature range: -30°C~80°C



Swivel Caster	Model								
	CP10P-PUP-SPS100.50	100*50	143	30	116*100*6	92 / 77*76 / 67	11	400	
CP10P-PUP-SPS125.50	125*50	164	38	116*100*6	92 / 77*76 / 67	11	420		
CP10P-PUP-SPS150.50	150*50	188	40	116*100*6	92 / 77*76 / 67	11	450		
CP10P-PUP-SPS200.50	200*50	236	58	116*100*6	92 / 77*76 / 67	11	500		

Rigid Caster	Model								
	CP10P-PUP-SPR100.50	100*50	143	/	116*100*6	92 / 77*76 / 67	11	400	
CP10P-PUP-SPR125.50	125*50	164	/	116*100*6	92 / 77*76 / 67	11	420		
CP10P-PUP-SPR150.50	150*50	188	/	116*100*6	92 / 77*76 / 67	11	450		
CP10P-PUP-SPR200.50	200*50	236	/	116*100*6	92 / 77*76 / 67	11	500		

Double Brake Caster	Model								
	CP10P-PUP-SPB100.50	100*50	143	30	116*100*6	92 / 77*76 / 67	11	400	
CP10P-PUP-SPB125.50	125*50	164	38	116*100*6	92 / 77*76 / 67	11	420		
CP10P-PUP-SPB150.50	150*50	188	40	116*100*6	92 / 77*76 / 67	11	450		
CP10P-PUP-SPB200.50	200*50	236	58	116*100*6	92 / 77*76 / 67	11	500		

Optional Wheels



Features & Advantages:

1. We can provide 360 day customized service
2. There are multiple styles for customers to choose from, including color, size, appearance and style
3. Strong bearing capacity, friction resistance, long life, can strictly meet international test standards according to customer requirements
4. The wheel bearing can rotate flexibly and its service life is increased

Specification:

Type: PU on PP Heavy Duty Casters	Surface Treatment: Zinc plated and painting
Wheel size(mm): 100*50 / 125*50 / 150*50 / 200*50	Tread Color: Gray and blue
Tread Material: PU	Applicable Temperature: -30°C~80°C
Mounting Height(mm): 143~236	Load Capacity(kgs): 400~500
Plate Thickness(mm): 6	Bearing Type: Ball bearings

Model No.: CP43

Product name: Stainless Steel Solid PU Casters

Optional Wheel: PU wheel, rubber wheel, nylon wheel, cast iron wheel, phenolic wheel, TPR wheel, anti-static wheel

Loading capacity: 150~300KGS

Housing: made of pressed stainless steel, double ballrace swivel head, dust proof seal

Wheel Material: Solid PU

Bearing Type: Delrin bearing

Temperature range: -30°C~90°C



Swivel Caster	Model	Icons representing various specifications									
		100*50	125*50	150*50	200*50	114*100*6	84*72	11	62*6	Delrin	Kg
	CP43SS-SP100.50	100*50	144	34	114*100*6	84*72	11	62*6	Delrin	150	
	CP43SS-SP125.50	125*50	165	38	114*100*6	84*72	11	62*6	Delrin	200	
	CP43SS-SP150.50	150*50	191	43	114*100*6	84*72	11	62*6	Delrin	250	
	CP43SS-SP200.50	200*50	241	53	114*100*6	84*72	11	62*6	Delrin	300	

Rigid Caster	Model	Icons representing various specifications									
		100*50	125*50	150*50	200*50	114*100*6	84*72	11	62*6	Delrin	Kg
	CP43SR-SP100.50	100*50	144	/	114*100*6	84*72	11	62*6	Delrin	150	
	CP43SR-SP125.50	125*50	165	/	114*100*6	84*72	11	62*6	Delrin	200	
	CP43SR-SP150.50	150*50	191	/	114*100*6	84*72	11	62*6	Delrin	250	
	CP43SR-SP200.50	200*50	241	/	114*100*6	84*72	11	62*6	Delrin	300	

Swivel with side brake	Model	Icons representing various specifications									
		100*50	125*50	150*50	200*50	114*100*6	84*72	11	62*6	Delrin	Kg
	CP43ST-SP100.50	100*50	144	34	114*100*6	84*72	11	62*6	Delrin	150	
	CP43ST-SP125.50	125*50	165	38	114*100*6	84*72	11	62*6	Delrin	200	
	CP43ST-SP150.50	150*50	191	43	114*100*6	84*72	11	62*6	Delrin	250	
	CP43ST-SP200.50	200*50	241	53	114*100*6	84*72	11	62*6	Delrin	300	

Optional Wheels



Features & Advantages:

1. Housing It adopts 6mm × 304 stainless steel plate and stainless steel double ballrace plate structure, with strong corrosion resistance. The surface of 100% washable polishing bracket can keep long-term brightness. It is suitable for heavy-duty mobile equipment in food processing, catering and other industries.
2. All Pu wheels are highly resistant to chemical corrosion and oil pollution, with strong stability.

Specification:

Type: Stainless Steel Solid PU Casters	Surface Treatment: Stainless steel
Wheel size(mm): 100*50 / 125*50 / 150*50 / 200*50	Tread Color: Blue
Tread Material: PU	Applicable Temperature: -30°C~90°C
Mounting Height(mm): 144~200	Load Capacity(kgs): 150~300
Plate Thickness(mm): 6	Bearing Type: Delrin bearings

Model No.: CP15

Product name: PU Heavy Duty Casters

Optional Wheel: PU on aluminium wheel, elastic PU on aluminium wheel, PU on cast

iron wheel, hard solid PU wheel, phenolic wheel

Loading capacity: 250~500KGS

Housing: made of pressed steel, double ballrace swivel head, dust proof seal

Wheel Material: Red PU on cast iron core wheel

Bearing Type: Precision Double ball bearings

Temperature range: -30°C~80°C



	Model	Wheel		Housing		Plate		Bearing		Kg
		Size	Load	Size	Load	Size	Load	Type	Capacity	
Swivel Caster	CP44S-P100.50	100*50	230	35	100*115*6	75*85	20*13	63*6	Ball bearing	250
	CP44S-P125.50	125*50	250	39	100*115*6	75*85	20*13	63*6	Ball bearing	350
	CP44S-P150.50	150*50	280	45	100*115*6	75*85	20*13	63*6	Ball bearing	450
	CP44S-P200.50	200*50	300	56	100*115*6	75*85	20*13	63*6	Ball bearing	500

	Model	Wheel		Housing		Plate		Bearing		Kg
		Size	Load	Size	Load	Size	Load	Type	Capacity	
Rigid Caster	CP44R-P100.50	100*50	230	/	100*115*6	75*85	20*13	63*6	Ball bearing	250
	CP44R-P125.50	125*50	250	/	100*115*6	75*85	20*13	63*6	Ball bearing	350
	CP44R-P150.50	150*50	280	/	100*115*6	75*85	20*13	63*6	Ball bearing	450
	CP44R-P200.50	200*50	300	/	100*115*6	75*85	20*13	63*6	Ball bearing	500

	Model	Wheel		Housing		Plate		Bearing		Kg
		Size	Load	Size	Load	Size	Load	Type	Capacity	
Swivel with side brake	CP44SB-P100.50	100*50	230	35	100*115*6	75*85	20*13	63*6	Ball bearing	250
	CP44SB-P125.50	125*50	250	39	100*115*6	75*85	20*13	63*6	Ball bearing	350
	CP44SB-P150.50	150*50	280	45	100*115*6	75*85	20*13	63*6	Ball bearing	450
	CP44SB-P200.50	200*50	300	56	100*115*6	75*85	20*13	63*6	Ball bearing	500

	Model	Wheel		Housing		Plate		Bearing		Kg
		Size	Load	Size	Load	Size	Load	Type	Capacity	
Swivel with total brake	CP44T-P100.50	100*50	230	35	100*115*6	75*85	20*13	63*6	Ball bearing	250
	CP44T-P125.50	125*50	250	39	100*115*6	75*85	20*13	63*6	Ball bearing	350
	CP44T-P150.50	150*50	280	45	100*115*6	75*85	20*13	63*6	Ball bearing	450
	CP44T-P200.50	200*50	300	56	100*115*6	75*85	20*13	63*6	Ball bearing	500

Optional Wheels




Features & Advantages:

1. The caster bracket produced by high-pressure punch is used for one-time stamping, which is suitable for the short distance transportation of 200-500kg load capacity goods.
2. The casters with various materials and width and load capacity can be selected according to the user's different use environment.
3. Different caster products can be designed according to the environmental bearing capacity required by users.
4. Environmental protection and abrasion resistance.

Specification:

Type: PU Heavy Duty Casters	Surface Treatment: Zinc plated
Wheel size(mm): 100*50 / 125*50 / 150*50 / 200*50	Tread Color: Red
Tread Material: PU	Applicable Temperature: -30°C~80°C
Mounting Height(mm): 230~300	Load Capacity(kgs): 250~500
Plate Thickness(mm): 6	Bearing Type: Double ball bearings

Model No.: CP45
 Product name: PU Shock Absorbing Casters
 Optional Wheel: PU on aluminium wheel, elastic PU on aluminium wheel, PU on cast iron wheel, hard solid PU wheel, phenolic wheel
 Loading capacity: 250~500KGS
 Housing: made of pressed steel, double ballrace swivel head, dust proof seal



Swivel Caster	Model										
		CP45S-PSA100.50	100*50	200	65	140*110*6	105*78	15	63*6	Ball bearing	300
	CP45S-PSA125.50	125*50	215	65	140*110*6	105*78	15	63*6	Ball bearing	350	
	CP45S-PSA150.50	150*50	227	65	140*110*6	105*78	15	63*6	Ball bearing	400	
	CP45S-PSA200.50	200*50	264	90	140*110*6	105*78	15	63*6	Ball bearing	500	

Rigid Caster	Model										
		CP45R-P100.50	100*50	143	/	140*110*6	105*78	15	63*6	Ball bearing	250
	CP45R-P125.50	125*50	165	/	140*110*6	105*78	15	63*6	Ball bearing	350	
	CP45R-P150.50	150*50	190	/	140*110*6	105*78	15	63*6	Ball bearing	450	
	CP45R-P200.50	200*50	240	/	140*110*6	105*78	15	63*6	Ball bearing	500	

Swivel with total brake	Model										
		CP45T-P100.50	100*50	143	35	140*110*6	105*78	15	63*6	Ball bearing	250
	CP45T-P125.50	125*50	165	39	140*110*6	105*78	15	63*6	Ball bearing	350	
	CP45T-P150.50	150*50	190	45	140*110*6	105*78	15	63*6	Ball bearing	450	
	CP45T-P200.50	200*50	240	56	140*110*6	105*78	15	63*6	Ball bearing	500	

Optional Wheels



Features & Advantages:

1. The high-pressure punch caster housing is used for one-time stamping, suitable for 200-500kg load capacity goods.
2. Round tread could realized much smoothness in capacity carrying.
3. Environmental friendly protection and stronger abrasion resistance.

Specification:

Type: PU Shock Absorbing Casters	Surface Treatment: Zinc Plated
Wheel size(mm): 100*50 / 125*50 / 150*50 / 200*50	Tread Color: Red
Tread Material: Red PU (on cast iron core wheel)	Applicable Temperature: -30°C-80°C
Mounting Height(mm): 200 / 215 / 227 / 264	Load Capacity(kgs): 300-500
Plate Thickness(mm): 6	Bearing Type: Precision Double ball bearings

Model No.: CP46

Product name: Rubber on Aluminium Casters

Optional Wheel: PU on aluminium wheel, elastic PU on aluminium wheel, PU on cast iron wheel, hard solid PU wheel, phenolic wheel

Loading capacity: 350~500KGS

Housing: made of pressed steel, double ballrace swivel head, dust proof seal



	Model	Tread		Housing		Plate		Bearing	Load Capacity (kg)	
		100*50	125*50	150*50	200*50	230	250			280
Swivel Caster	CP46S-RA100.50	100*50	230	35	100*115*6	75*85	20*13	63*6	Ball bearing	250
	CP46S-RA125.50	125*50	250	39	100*115*6	75*85	20*13	63*6	Ball bearing	350
	CP46S-RA150.50	150*50	280	45	100*115*6	75*85	20*13	63*6	Ball bearing	450
	CP46S-RA200.50	200*50	300	56	100*115*6	75*85	20*13	63*6	Ball bearing	500

	Model	Tread		Housing		Plate		Bearing	Load Capacity (kg)	
		100*50	125*50	150*50	200*50	230	250			280
Rigid Caster	CP46R-RA100.50	100*50	230	35	100*115*6	75*85	20*13	63*6	Ball bearing	250
	CP46R-RA125.50	125*50	250	39	100*115*6	75*85	20*13	63*6	Ball bearing	350
	CP46R-RA150.50	150*50	280	45	100*115*6	75*85	20*13	63*6	Ball bearing	450
	CP46R-RA200.50	200*50	300	56	100*115*6	75*85	20*13	63*6	Ball bearing	500

	Model	Tread		Housing		Plate		Bearing	Load Capacity (kg)	
		100*50	125*50	150*50	200*50	230	250			280
Swivel with side brake	CP46SB-RA100.50	100*50	230	35	100*115*6	75*85	20*13	63*6	Ball bearing	250
	CP46SB-RA125.50	125*50	250	39	100*115*6	75*85	20*13	63*6	Ball bearing	350
	CP46SB-RA150.50	150*50	280	45	100*115*6	75*85	20*13	63*6	Ball bearing	450
	CP46SB-RA200.50	200*50	300	56	100*115*6	75*85	20*13	63*6	Ball bearing	500

	Model	Tread		Housing		Plate		Bearing	Load Capacity (kg)	
		100*50	125*50	150*50	200*50	230	250			280
Swivel with total brake	CP46T-RA100.50	100*50	230	35	100*115*6	75*85	20*13	63*6	Ball bearing	250
	CP46T-RA125.50	125*50	250	39	100*115*6	75*85	20*13	63*6	Ball bearing	350
	CP46T-RA150.50	150*50	280	45	100*115*6	75*85	20*13	63*6	Ball bearing	450
	CP46T-RA200.50	200*50	300	56	100*115*6	75*85	20*13	63*6	Ball bearing	500

Optional Wheels



Features & Advantages:

Tread:

1. High load capacity;
2. Non marking
3. Shock absorbing
4. Noiseless
5. ECO-friendly

Wheel Core:

1. Heat release quickly
2. Heavy loading and strong structure
3. Light net weight for easy pushing

Specification:

Type: Industrial Rubber on Aluminium Casters	Surface Treatment: Zinc Plated
Wheel size(mm): 100*50 / 125*50 / 150*50 / 200*50	Tread Color: Black
Tread Material: Rubber (on aluminium core wheel)	Applicable Temperature: -30°C~80°C
Mounting Height(mm): 230 / 250 / 280 / 300	Load Capacity(kgs): 300~500
Plate Thickness(mm): 6	Bearing Type: Precision Double ball bearings

Model No.: CP47

Product name: Round PU on Cast Iron Casters

Optional Wheel: PU on aluminium wheel, elastic PU on aluminium wheel, PU on cast iron wheel, hard solid PU wheel, phenolic wheel

Loading capacity: 250~600KGS

Housing: zinc plated made of pressed steel, double ballrace swivel head, dust proof seal



	Model	Tread		Wheel		Housing		Bearing	Capacity (kg)	
		Ø	W	H	W	H	W			
Swivel Caster	CP47S-RPC100.50	100*50	135	35	100*115*6	72*85	20*13	63*6	Ball bearing	250
	CP47S-RPC125.50	125*50	159	39	100*115*6	72*85	20*13	63*6	Ball bearing	350
	CP47S-RPC150.50	150*50	189	45	100*115*6	72*85	20*13	63*6	Ball bearing	500
	CP47S-RPC200.50	200*50	238	56	100*115*6	72*85	20*13	63*6	Ball bearing	600

	Model	Tread		Wheel		Housing		Bearing	Capacity (kg)	
		Ø	W	H	W	H	W			
Rigid Caster	CP47R-RPC100.50	100*50	135	/	100*115*6	72*85	20*13	63*6	Ball bearing	250
	CP47R-RPC125.50	125*50	159	/	100*115*6	72*85	20*13	63*6	Ball bearing	350
	CP47R-RPC150.50	150*50	189	/	100*115*6	72*85	20*13	63*6	Ball bearing	500
	CP47R-RPC200.50	200*50	238	/	100*115*6	72*85	20*13	63*6	Ball bearing	600

	Model	Tread		Wheel		Housing		Bearing	Capacity (kg)	
		Ø	W	H	W	H	W			
Swivel with side brake	CP47SB-RPC100.50	100*50	135	35	100*115*6	72*85	20*13	63*6	Ball bearing	250
	CP47SB-RPC125.50	125*50	159	39	100*115*6	72*85	20*13	63*6	Ball bearing	350
	CP47SB-RPC150.50	150*50	189	45	100*115*6	72*85	20*13	63*6	Ball bearing	500
	CP47SB-RPC200.50	200*50	238	56	100*115*6	72*85	20*13	63*6	Ball bearing	600

	Model	Tread		Wheel		Housing		Bearing	Capacity (kg)	
		Ø	W	H	W	H	W			
Swivel with total brake	CP47T-RPC100.50	100*50	135	35	100*115*6	72*85	20*13	63*6	Ball bearing	250
	CP47T-RPC125.50	125*50	159	39	100*115*6	72*85	20*13	63*6	Ball bearing	350
	CP47T-RPC150.50	150*50	189	45	100*115*6	72*85	20*13	63*6	Ball bearing	500
	CP47T-RPC200.50	200*50	238	56	100*115*6	72*85	20*13	63*6	Ball bearing	600

Optional Wheels



Features & Advantages:

Tread:

1. Non Marking and Non Conductive.
2. ECO-friendly
3. Round wheel tread, super easy moving
4. Pure color without released bubble ,industrial appearance
5. Strict test, up to 600 kgs per wheel

Wheel Core:

1. Heavy loading and strong structure
2. Industrial standard design with technician artwork, long lifetime span

Specification:

Type: Industrial PU on Iron Casters	Surface Treatment: Zinc Plated
Wheel size(mm): 100*50 / 125*50 / 150*50 / 200*50	Tread Color: Red
Tread Material: PU(on cast iron core wheel)	Applicable Temperature: -25℃~80℃
Mounting Height(mm): 135 / 159 / 189 / 238	Load Capacity(kgs): 250~600
Plate Thickness(mm): 5 / 6	Bearing Type: Precision Double ball bearings

Model No.: CP48
 Product name: Industrial Cast Iron Casters
 Optional Wheel: PU on aluminium wheel, elastic PU on aluminium wheel, PU on cast iron wheel, hard solid PU wheel, phenolic wheel
 Loading capacity: 270~400KGS
 Housing: zinc plated made of pressed steel, double ballrace swivel head, dust proof seal



Swivel Caster	Model	Dimensions (mm)				Wheel Size (mm)			Bearing	Load Capacity (kg)
		W	H	W	H	W	H	W		
	CP48S-CI100.50	100*50	142	35	114*98*6	84*71	21*12	63*6	Ball bearing	270
	CP48S-CI125.50	125*50	165	39	114*98*6	84*71	21*12	63*6	Ball bearing	320
	CP48S-CI150.50	150*50	191	45	114*98*6	84*71	21*12	63*6	Ball bearing	350
	CP48S-CI200.50	200*50	240	56	114*98*6	84*71	21*12	63*6	Ball bearing	400

Rigid Caster	Model	Dimensions (mm)				Wheel Size (mm)			Bearing	Load Capacity (kg)
		W	H	W	H	W	H	W		
	CP48R-CI100.50	100*50	142	/	114*98*6	84*71	21*12	63*6	Ball bearing	270
	CP48R-CI125.50	125*50	165	/	114*98*6	84*71	21*12	63*6	Ball bearing	320
	CP48R-CI150.50	150*50	191	/	114*98*6	84*71	21*12	63*6	Ball bearing	350
	CP48R-CI200.50	200*50	240	/	114*98*6	84*71	21*12	63*6	Ball bearing	400

Swivel with total brake	Model	Dimensions (mm)				Wheel Size (mm)			Bearing	Load Capacity (kg)
		W	H	W	H	W	H	W		
	CP48T-CI100.50	100*50	142	35	114*98*6	84*71	21*12	63*6	Ball bearing	270
	CP48T-CI125.50	125*50	165	39	114*98*6	84*71	21*12	63*6	Ball bearing	320
	CP48T-CI150.50	150*50	191	45	114*98*6	84*71	21*12	63*6	Ball bearing	350
	CP48T-CI200.50	200*50	240	56	114*98*6	84*71	21*12	63*6	Ball bearing	400

Optional Wheels



Features & Advantages:

Tread:

1. High load capacity
2. 800 degree heat resistance
3. Great wear-resistant capacity
4. Strict running testing, up to 400 kgs per wheel

Wheel Core:

1. Heavy loading and strong structure
2. Industrial standard design with technician artwork, long lifetime span
3. Smooth precision double ball bearings and anti rust finish

Specification:

Type: Industrial Cast Iron Casters	Surface Treatment: Zinc Plated
Wheel size(mm): 100*50 / 125*50 / 150*50 / 200*50	Tread Color: Dark grey
Tread Material: Cast iron core	Applicable Temperature: -30°C~800°C
Mounting Height(mm): 142 / 165 / 191 / 240	Load Capacity(kgs): 270~400
Plate Thickness(mm): 6	Bearing Type: Precision Double ball bearings

Model No.: CP49
 Product name: PU on Aluminium Casters
 Optional Wheel: PU on aluminium wheel, elastic PU on aluminium wheel, PU on cast iron wheel, hard solid PU wheel, phenolic wheel
 Loading capacity: 300~500KGS
 Housing: zinc plated, made of pressed steel, double ballrace swivel head, dust proof seal



Swivel Caster	Model	Icons																				
		100*50	125*50	150*50	200*50	250*50	142	164	190	240	280	35	39	45	56	71	115*100*6	85*72	19*10	63*6	Ball bearing	Kg
	CP49S-PA100.50	100*50	125*50	150*50	200*50	250*50	142	164	190	240	280	35	39	45	56	71	115*100*6	85*72	19*10	63*6	Ball bearing	300
	CP49S-PA125.50	100*50	125*50	150*50	200*50	250*50	142	164	190	240	280	35	39	45	56	71	115*100*6	85*72	19*10	63*6	Ball bearing	350
	CP49S-PA150.50	100*50	125*50	150*50	200*50	250*50	142	164	190	240	280	35	39	45	56	71	115*100*6	85*72	19*10	63*6	Ball bearing	400
	CP49S-PA200.50	100*50	125*50	150*50	200*50	250*50	142	164	190	240	280	35	39	45	56	71	115*100*6	85*72	19*10	63*6	Ball bearing	450
	CP49S-PA250.50	100*50	125*50	150*50	200*50	250*50	142	164	190	240	280	35	39	45	56	71	115*100*6	85*72	19*10	63*6	Ball bearing	500

Rigid Caster	Model	Icons																				
		100*50	125*50	150*50	200*50	250*50	142	164	190	240	280	/	/	/	/	/	115*100*6	85*72	19*10	63*6	Ball bearing	Kg
	CP49R-PA100.50	100*50	125*50	150*50	200*50	250*50	142	164	190	240	280	/	/	/	/	/	115*100*6	85*72	19*10	63*6	Ball bearing	300
	CP49R-PA125.50	100*50	125*50	150*50	200*50	250*50	142	164	190	240	280	/	/	/	/	/	115*100*6	85*72	19*10	63*6	Ball bearing	350
	CP49R-PA150.50	100*50	125*50	150*50	200*50	250*50	142	164	190	240	280	/	/	/	/	/	115*100*6	85*72	19*10	63*6	Ball bearing	400
	CP49R-PA200.50	100*50	125*50	150*50	200*50	250*50	142	164	190	240	280	/	/	/	/	/	115*100*6	85*72	19*10	63*6	Ball bearing	450
	CP49R-PA250.50	100*50	125*50	150*50	200*50	250*50	142	164	190	240	280	/	/	/	/	/	115*100*6	85*72	19*10	63*6	Ball bearing	500

Swivel with side brake	Model	Icons																				
		100*50	125*50	150*50	200*50	250*50	142	164	190	240	280	35	39	45	56	71	115*100*6	85*72	19*10	63*6	Ball bearing	Kg
	CP49SB-PA100.50	100*50	125*50	150*50	200*50	250*50	142	164	190	240	280	35	39	45	56	71	115*100*6	85*72	19*10	63*6	Ball bearing	300
	CP49SB-PA125.50	100*50	125*50	150*50	200*50	250*50	142	164	190	240	280	35	39	45	56	71	115*100*6	85*72	19*10	63*6	Ball bearing	350
	CP49SB-PA150.50	100*50	125*50	150*50	200*50	250*50	142	164	190	240	280	35	39	45	56	71	115*100*6	85*72	19*10	63*6	Ball bearing	400
	CP49SB-PA200.50	100*50	125*50	150*50	200*50	250*50	142	164	190	240	280	35	39	45	56	71	115*100*6	85*72	19*10	63*6	Ball bearing	450
	CP49SB-PA250.50	100*50	125*50	150*50	200*50	250*50	142	164	190	240	280	35	39	45	56	71	115*100*6	85*72	19*10	63*6	Ball bearing	500

Swivel with total brake	Model	Icons																				
		100*50	125*50	150*50	200*50	250*50	142	164	190	240	280	35	39	45	56	71	115*100*6	85*72	19*10	63*6	Ball bearing	Kg
	CP49T-PA100.50	100*50	125*50	150*50	200*50	250*50	142	164	190	240	280	35	39	45	56	71	115*100*6	85*72	19*10	63*6	Ball bearing	300
	CP49T-PA125.50	100*50	125*50	150*50	200*50	250*50	142	164	190	240	280	35	39	45	56	71	115*100*6	85*72	19*10	63*6	Ball bearing	350
	CP49T-PA150.50	100*50	125*50	150*50	200*50	250*50	142	164	190	240	280	35	39	45	56	71	115*100*6	85*72	19*10	63*6	Ball bearing	400
	CP49T-PA200.50	100*50	125*50	150*50	200*50	250*50	142	164	190	240	280	35	39	45	56	71	115*100*6	85*72	19*10	63*6	Ball bearing	450
	CP49T-PA250.50	100*50	125*50	150*50	200*50	250*50	142	164	190	240	280	35	39	45	56	71	115*100*6	85*72	19*10	63*6	Ball bearing	500

Optional Wheels



Features & Advantages:

Tread:

1. High load capacity, up to 500 kgs per wheel
2. Aluminum core with uniquely formulated polyurethane tread provides optimal floor protection and rollability
3. Anti-corrosion

Wheel Core:

1. Round design for accurate capacity application for longer lifetime span
2. Smooth precision double ball bearings and anti rust finish

Specification:

Type: Industrial PU on Aluminium Casters	Surface Treatment: Zinc Plated
Wheel size(mm): 100*50 / 125*50 / 150*50 / 200*50 / 250*50	Tread Color: Yellow
Tread Material: PU(on aluminium core)	Applicable Temperature: -30°C~80°C
Mounting Height(mm): 142 / 164 / 190 / 240 / 280	Load Capacity(kgs): 300~500
Plate Thickness(mm): 6	Bearing Type: Precision Double ball bearings



Heavy Duty Casters

Model No.: CP50

Product name: Industrial PU Twin Wheel Casters

Optional Wheel: PU on aluminium wheel, elastic PU on aluminium wheel, PU on cast

iron wheel, hard solid PU wheel, phenolic wheel

Loading capacity: 3000~5000KGS



Swivel Caster	Model							
	CP50S-TP150.70	150*70	263	177*135	140*106	18	Double Ball bearing 206	3000
CP50S-TP200.70	200*70	301	177*135	140*106	18	Double Ball bearing 206	3500	
CP50S-TP250.70	250*70	339	177*135	140*106	18	Double Ball bearing 206	4000	
CP50S-TP300.70	300*70	393	177*135	140*106	18	Double Ball bearing 206	5000	

Rigid Caster	Model							
	CP50R-TP150.70	150*70	263	177*135	140*106	18	Double Ball bearing 206	3000
CP50R-TP200.70	200*70	301	177*135	140*106	18	Double Ball bearing 206	3500	
CP50R-TP250.70	150*70	339	177*135	140*106	18	Double Ball bearing 206	4000	
CP50R-TP300.70	200*70	393	177*135	140*106	18	Double Ball bearing 206	5000	

Features & Advantages:

1. The wheel is made of PU coated black painted cast iron wheel, and the hardness of Pu can reach Shore 95° A
2. The rotating structure of the bracket adopts double bead groove structure, the hardness of the ball bowl heat treatment reaches HRC45-50, and the ball heat treatment is more flexible
3. The bracket is welded with CO2 protection, and the weld is in good shape
4. The good choice of handling large heavy machinery and equipment

Specification:

Type: Extra Heavy Duty Twin Wheel Casters	Surface Treatment: Zinc Plated
Wheel size(mm): 150*70 / 200*70 / 250*70 / 300*70	Tread Color: Red
Tread Material: cast iron core	Applicable Temperature: -30℃~80℃
Mounting Height(mm): 263 / 301 / 339 / 393	Load Capacity(kgs): 3000~5000
Plate Thickness(mm): 25~30	Bearing Type: Precision Double ball bearings



Model No.: CP51

Product name: Heavy Duty TPR on PP Casters

Optional Wheel: PU on aluminium wheel, elastic PU on aluminium wheel, PU on cast iron wheel, hard solid PU wheel, phenolic wheel

Loading capacity: 230~320KGS

Housing: zinc plated made of pressed steel, double ballrace swivel head, dust proof seal



Swivel Caster	Model									
	CP51S-TP100.50	100*50	142	35	115*100*5.5	75*85	20*13	63*5	Ball bearing	230
CP51S-TP125.50	125*50	166	39	115*100*5.5	75*85	20*13	63*5	Ball bearing	280	
CP51S-TP150.50	150*50	195	45	115*100*5.5	75*85	20*13	63*5	Ball bearing	300	
CP51S-TP200.50	200*50	240	56	115*100*5.5	75*85	20*13	63*5	Ball bearing	320	

Rigid Caster	Model									
	CP51R-TP100.50	100*50	142	/	115*100*5.5	75*85	20*13	63*5	Ball bearing	230
CP51R-TP125.50	125*50	166	/	115*100*5.5	75*85	20*13	63*5	Ball bearing	280	
CP51R-TP150.50	150*50	195	/	115*100*5.5	75*85	20*13	63*5	Ball bearing	300	
CP51R-TP200.50	200*50	240	/	115*100*5.5	75*85	20*13	63*5	Ball bearing	320	

Swivel with total brake	Model									
	CP51T-TP100.50	100*50	142	35	115*100*5.5	75*85	20*13	63*5	Ball bearing	230
CP51T-TP125.50	125*50	166	39	115*100*5.5	75*85	20*13	63*5	Ball bearing	280	
CP51T-TP150.50	150*50	195	45	115*100*5.5	75*85	20*13	63*5	Ball bearing	300	
CP51T-TP200.50	200*50	240	56	115*100*5.5	75*85	20*13	63*5	Ball bearing	320	

Optional Wheels



Features & Advantages:

1. High quality elastic rubber material is used to cushion and compress
2. Thick board, high material strength, strong and durable, firm installation
3. The galvanized bracket without dead angle is anti-corrosion, thick and load-bearing

Specification:

Type: Heavy Duty TPR on PP Casters	Surface Treatment: Zinc Plated
Wheel size(mm): 100*50 / 125*50 / 150*50 / 200*50	Tread Color: Blue / Gray
Tread Material: TPR	Applicable Temperature: -30°C~800°C
Mounting Height(mm): 142 / 166 / 195 / 240	Load Capacity(kgs): 230~320
Plate Thickness(mm): 5.5	Bearing Type: Precision Double ball bearings

Model No.: CP81
 Product name: Square Top Plate Leveling Adjustable Casters
 Optional Wheel: NA
 Loading capacity: 50~1500KGS
 Housing: sprayed and galvanized, with baseboard carbon steel / stainless steel stamping

CP22GD-F Series



Model		Tread width (mm)	Mount height (mm)	Top-plate thickness (mm)	Top-plate size(mm)	Top-plate hole distance (mm)	Top Hole Size(mm)	Adjust ground height (mm)	Single wheel load(mm)	2 wheel load(KGS)
CP81GD-40F		42	20	4	55*55	42*42	6.5	10	50	100
CP81GD-60F		50	25	4.5	73*73	58*58	7	10	250	500
CP81GD-80F		63	30	5	92*92	70*70	9	15	500	1000
CP81GD-100F		75	30	6	92*92	70*70	9	12	750	1500
CP81GD-120F		75	30	6	95*95	70*70	11	12	1000	2000
CP81GD-150F		90	55	8.5	100*100	70*70	13	15	1500	3000

Features & Advantages:

1. Convenient for the movement of equipment, adjusting the level, positioning and anti-vibration
2. The center has adjustable foot seat, non-sway structure, excellent installation, fashionable and beautiful, practical and so on.
3. Different models adopt different packaging sizes (including outer and inner boxes), which is convenient to calculate volume and make full use of packaging space, saving transportation and labor costs.

Specification:

Type: Square Top Plate Leveling Adjustable Casters	Surface Treatment: Baseboard: carbon steel / stainless steel; Adjust: M C Nylon; Housing: Aluminium alloy; Base: Aluminium alloy; Foot: NBR/M C Nylon
Wheel size(mm): 42*20 / 50*25 / 63*30 / 75*30 / 90*55	Color: Milk white/coffee
Tread Material: MC Nylon	Applicable Temperature: -15°C~70°C
Mounting Height(mm): 71 / 82 / 103 / 120 / 132	Load Capacity(kgs): 50~1500
Plate Thickness(mm): 4~8.5	Bearing Type: Sliding bearings

Model No.: CP82
 Product name: Polygonal Top Plate Leveling Casters
 Optional Wheel: NA
 Loading capacity: 50~1500KGS
 Housing: sprayed and galvanized, with baseboard carbon steel / stainless steel stamping.

CP22GD-S Series



Model		Tread width (mm)	Mount height (mm)	Top-plate	Stem Length (mm)	Stem Dia. (mm)	Adjust ground height (mm)	Single wheel load(mm)	2 wheel load(KGS)
CP82GD-40S	42	20	71	Octagon	10	M8	10	50	100
CP82GD-60S	50	25	82	Octagon	15	M12	10	250	500
CP82GD-80S	63	30	103	Octagon	15	M12	15	500	1000
CP82GD-100S	75	30	120	Octagon	20	M16	12	750	1500
CP82GD-120S	75	30	120	Octagon	20	M16	12	1000	2000

Features & Advantages:

1. Cast aluminum frame with steel rotating head and internal leveling mechanism, dial with rubber foot pad to level the foot pad, and make the attached equipment completely fixed.
2. The powder coating decorative panel is installed with super strong unmarked nylon wheel.
3. Our brand has a new and improved special design that makes lever adjustment easier to use by hand.
4. Different models adopt different packaging carton sizes (including outer and inner boxes), which is convenient to calculate volume and make full use of packaging space, saving transportation and labor costs.

Specification:

Type: Polygonal Top Plate Leveling Casters	Surface Treatment: Baseboard: carbon steel/stainless steel; Adjust: M C Nylon; Housing: Aluminium alloy; Base: Aluminium alloy; Foot: NBR/M C Nylon
Wheel size(mm): 42*20 / 50*25 / 63*30 / 75*30 / 90*55	Tread Color: Black/blue
Tread Material: MC Nylon	Applicable Temperature: -15°C~70°C
Mounting Height(mm): 71 / 82 / 103 / 120 / 132	Load Capacity(kgs): 50~1500
Plate Thickness(mm): 4~8.5	Bearing Type: Sliding bearings

Model No.: CP83
 Product name: Nylon Airport Cargo Casters
 Optional Wheel: NA
 Loading capacity: 200KGS
 Housing: zinc plated, yellow Passivated Coating



Swivel Casters



Model								
CP24-AC58.35-1	58*34	96	25	111*80*3	86*61	4 / 2	Ball bearing	200
CP24-AC58.35-2	58*34	96	25	111*80*3	86*61	4 / 2	Ball bearing	200

Features & Advantages:

1. Abrasion resistant
2. Shock resistant
3. Sealed Swivel Bearing
4. Rounded Metal guards to prevent debris from entering bearing

Specification:

Type: Airport Cargo Casters	Surface Treatment: Zinc Plated and yellow Passivated Coating
Wheel size(mm): 58*35	Tread Color: White
Tread Material: Nylon	Applicable Temperature: -30°C~80°C
Mounting Height(mm): 96	Load Capacity(kgs): 200
Plate Thickness(mm): 3	Bearing Type: Ball bearings

Model No.: CP84
 Product name: Swivel Scaffolding Casters with Rear Brake Optional
 Wheel: Rubber on Cast Iron Wheel / PU on Cast Iron Wheel / PU on PP Wheel
 Loading capacity: 150~250KGS
 Housing: Pressed steel housing, zinc plated, double ballrace swivel head

Standard 5inch / 6inch / 8inch adjustable scaffolding casters series with brake



CP84RB-SC-1 CP84RB-SC-2 CP84RB-SC-3

Model						Bore Dia. (L*W)	Hub Length (mm)				
Rubber on Cast Iron	PU on Cast Iron	PU on PP									
CP84RB-SC125.50-1	CP25RB-SC125.50-2	CP25RB-SC125.50-3	125*50	164	50	19	60	35*100	63*6	Roller bearing	150
CP84RB-SC150.50-1	CP25RB-SC150.50-2	CP25RB-SC150.50-3	150*50	190	50	19	60	35*100	63*6	Roller bearing	200
CP84RB-SC200.50-1	CP25RB-SC200.50-2	CP25RB-SC200.50-3	200*50	240	50	19	60	35*100	63*6	Roller bearing	250

Optional Wheels



Features & Advantages:

1. Double locked wheels and robust construction including cast iron hub and grease fitting adapter
2. Casters fit most scaffolding brands
3. The scaffold system has the characteristics of high cost-effective, durable and easy to install. It is suitable for indoor and outdoor construction.
4. Caster with gear plate and wheel brake. Double locking system, locking the rotating plate and wheels. With this kind of caster, you can move your scaffold flexibly and fix it stably
5. Use with standard or arched frames
6. Meet all OSHA and CSA requirements
7. Wheels wrapped in polyurethane make less noise than any other traditional material. The iron wheel hub not only makes the bearing heavier, but also makes the bearing hole have better wear resistance

Specification:

Type: Swivel Scaffolding Casters with Rear Brake	Brake: Swivel / Double brake
Surface Treatment: Zinc Plated	Artwork: Welding
Structure: Double Track, Durable and Reliable	Wheel Color: Black / Red
Load Capacity(KGS): 150 / 200 / 250	Wheel Size(MM): 125*50 / 150*50 / 200*50
Bearing: Roller bearing	Wheel Material: Rubber on Cast Iron / PU on Cast Iron / PU on PP
	Height(MM): 164 / 190 / 240

Model No.: CP85
 Product name: Total Brake Swivel Scaffolding Casters
 Optional Wheel: mold on rubber wheel, PU on cast iron wheel, PU on PP, TPR
 Loading capacity: 120~250KGS
 Housing: zinc plated, made of pressed steel, double ballrace swivel head, dust proof seal

Standard 4inch / 5inch / 6inch / 8inch scaffolding casters with total brake



CP85ST-SC-1 CP85ST-SC-2 CP85ST-SC-3 CP85ST-SC-4

Model							Bore Dia. (L*W)	Hub Length (mm)				
Rubber on Cast Iron	PU on Cast Iron	PU on PP	TPR									
CP85ST-SC100.50-1	CP85ST-SC100.50-2	CP85ST-SC100.50-3	CP85ST-SC100.50-4	100*50	142	35	19	60	38*100	62*6	Roller bearing	120
CP85ST-SC125.50-1	CP85ST-SC125.50-2	CP85ST-SC125.50-3	CP85ST-SC125.50-4	125*50	164	39	19	60	38*100	62*6	Roller bearing	150
CP85ST-SC150.50-1	CP85ST-SC150.50-2	CP85ST-SC150.50-3	CP85ST-SC150.50-4	150*50	190	45	19	60	38*100	62*6	Roller bearing	200
CP85ST-SC200.50-1	CP85ST-SC200.50-2	CP85ST-SC200.50-3	CP85ST-SC200.50-4	200*50	240	56	19	60	38*100	62*6	Roller bearing	250

8inch PU on Nylon / Nylon scaffolding casters with total brake



CP85ST-SC-5 CP85ST-SC-6

Model												
PU on Nylon	Nylon	PU on Nylon	Nylon	PU on Nylon	Nylon							
CP85ST-SC204.50-5	CP85ST-SC202.45-6	204*50	202*45	20*60	20*58	56	240	59*100	62*6	Plain bearing	400	

Optional Wheels



Features & Advantages:

1. The design of the scaffolding caster takes safety into consideration and provides high quality and extreme durability for all your scaffolds
2. High quality steel for frame and supporting accessories
3. High quality powder coated finish and galvanized finish, durable
4. Traceability stamp code on scaffold frame and scaffold parts for quality assurance

Specification:

Type: Total Brake Swivel Scaffolding Casters	Brake: Swivel with total brake	
Surface Treatment: Zinc Plated	Artwork: Welding	
Structure: Double Trace way, Durable and Reliable	Wheel Color: Black / Red / Gray	
Load Capacity(KGS): 120 / 150 / 200 / 250	Wheel Size(MM): 100*50 / 125*50 / 150*50 / 200*50	
Bearing: Roller bearing	Wheel Material: Rubber / PU / Plastic	Height(MM): 142 / 164 / 190 / 240

Model No.: CP86

Product name: Double Brake Fitting Fork Scaffolding Casters

Optional Wheel: PU on nylon wheel, nylon wheel

Loading capacity: 800KGS

Housing: zinc plated, made of pressed steel, double ballrace swivel head, dust proof seal

8inch adjustable scaffolding casters with double brake fitting fork



Material	Stem Top	Square Top				Bore Dia. (L*W)	Hub Length (mm)				
PU on Nylon	CP86ST-SC200.50-7	CP86T-SC200.50-1	200*50	243	40	12	61	38*100	63*4	Plain bearing	800
Nylon	CP86ST-SC200.50-8	CP86T-SC200.50-2	200*50	241	40	12	61	38*100	63*4	Plain bearing	800

Optional Wheels



Features & Advantages:

1. Full lock brake: easy to rotate and wheel engagement
2. Rotation and hub for easy lubrication
3. Seal swivel part: prevent debris from entering
4. Main bolt: main bolt and nut

Specification:

Type: Double Brake Fitting Fork Scaffolding Casters	Brake: Swivel fitting fork Double brake	
Surface Treatment: Zinc Plated	Artwork: Welding	
Structure: Double Track, Durable and Reliable	Wheel Color: White / Red	
Load Capacity(KGS): 800	Wheel Size(MM): 200*50	
Bearing: Roller bearing	Wheel Material: PU on nylon / nylon	Height(MM): 243 / 241



PU Wheels

Model No.: CP116
 Product name: Heavy Duty Solid PU Casters
 Loading capacity: 150~690KGS
 Wheel material: Industrial solid PU



Solid PU wheel with plain or roller bearing core	Model			Hub Length (mm)	Wheel Core(mm)	Bore Dia.(mm)		
	CP116-SPW75.31-1	75	31	39	12.5	9.4	plain	150
	CP116-SPW100.31-1	100	31	39	12.5	9.4	plain	180
	CP116-SPW125.31-1	125	31	39	12.5	9.4	plain	210
	CP116-SPW150.31-1	150	31	39	12.5	9.4	plain	230
	CP116-SPW100.50-1	100	50	54.5	29.5	12.5	bearing	290
	CP116-SPW125.50-1	125	50	54.5	29.5	12.5	bearing	350
	CP116-SPW150.50-1	150	50	54.5	29.5	12.5	bearing	400
	CP116-SPW200.50-1	200	50	54.5	29.5	12.5	bearing	460

Solid PU on steel hub wheel with ball bearings	Model			Hub Length (mm)	Wheel Core(mm)	Bore Dia.(mm)		
	CP116SPW100.50-2	100	50	54.5	40	17	Ball bearing	270
	CP116SPW125.50-2	125	50	54.5	47	20	Ball bearing	340
	CP116SPW150.50-2	150	50	54.5	47	20	Ball bearing	395
	CP116SPW200.50-2	200	50	54.5	47	20	Ball bearing	445
	CP116SPW150.62-2	150	62.5	81.3	52	25	Ball bearing	490
	CP116SPW200.62-2	200	62.5	81.3	52	25	Ball bearing	540
	CP116SPW250.62-2	250	62.5	81.3	52	25	Ball bearing	595
	CP116SPW150.75-2	150	75	81.3	52	25	Ball bearing	545
	CP116SPW200.75-2	200	75	81.3	52	25	Ball bearing	595
	CP116SPW250.75-2	250	75	81.3	52	25	Ball bearing	640
	CP116SPW200.75-2	300	75	81.3	52	25	Ball bearing	690

Specification:

Type: Heavy Duty Solid PU Casters	Tread Color: Dark Blue
Wheel Diameter: 3 inch ~ 12 inch	Applicable Temperature: -30°C ~ 80°C
Core Material: Industrial solid PU or Steel core	Load Capacity(kgs): 150 ~ 690
Hardness: 65D	Bearing Type: Plain bearing / roller bearing or Precision Double ball bearings



Model No.: CP117
 Product name: Industrial PU on PP Wheels
 Loading capacity: 100~400KGS
 Wheel material: PU on PP core wheel



PU on PP with plain or roller bearing



CP117PPW

Model			Hub Length (mm)	Wheel Core(mm)	Bore Dia.(mm)		
							kg
CP117-PPW75.31	75	31	40.6	28.1	9.4	plain	100
CP117-PPW100.31	100	31	40.6	28.1	9.4	plain	100
CP117-PPW125.31	125	31	40.6	28.1	9.4	plain	100
CP117-PPW100.37	100	37.5	40.6	12.5	9.4	Roller	210
CP117-PPW125.37	125	37.5	40.6	29.5	12.5	Roller	240
CP117-PPW150.37	150	37.5	40.6	29.5	12.5	Roller	260
CP117-PPW100.50	100	50	54.5	29.5	12.5	Roller	260
CP117-PPW125.50	125	50	54.5	29.5	12.5	Roller	310
CP117-PPW150.50	150	50	54.5	29.5	12.5	Roller	370
CP117-PPW200.50	200	50	54.5	29.5	12.5	Roller	400

Specification:

Type: Industrial PU on PP Wheels	Tread Color: Red
Wheel Diameter: 3 inch ~ 8 inch	Applicable Temperature: -30°C ~ 80°C
Core Material: Black PP core	Load Capacity(kgs): 100 ~ 400
Hardness: 93° shore A	Bearing Type: Plain bearing / roller bearing

Model No.: CP118
 Product name: PU on Iron Roller Bearing Wheels
 Loading capacity: 200~400KGS
 Wheel material: PU on Cast Iron core wheel



PU on Iron with roller bearing



CP118PCRW

Model			Hub Length (mm)	Wheel Core(mm)	Bore Dia.(mm)		
CP118-PCRW100.37	100	50	60	29.5	19	Roller	200
CP118-PCRW125.37	125	50	60	29.5	19	Roller	250
CP118-PCRW150.37	150	50	60	29.5	19	Roller	300
CP118-PCRW200.50	200	50	60	29.5	19	Roller	350
CP118-PCRW250.50	250	50	60	29.5	19	Roller	400

Specification:

Type: PU on Iron Roller Bearing Wheels	Tread Color: Red
Wheel Diameter: 4 inch ~ 10 inch	Applicable Temperature: -25°C ~ 80°C
Core Material: Cast Iron core	Load Capacity(kgs): 200 ~ 400
Hardness: 93° shore A	Bearing Type: Roller bearing

Model No.: CP119
 Product name: PU on Iron Ball Bearing Wheels
 Loading capacity: 320~500KGS
 Wheel material: PU on Cast Iron core wheel



PU on Iron with precision ball bearing



CP31PCBW

Model			Hub Length (mm)	Wheel Core(mm)	Bore Dia.(mm)		
CP119-PCBW100.50	100	50	55.6	40	17	Ball bearing	320
CP119-PCBW125.50	125	50	55.6	40	17	Ball bearing	400
CP119-PCBW150.50	150	50	55.6	40	17	Ball bearing	450
CP119-PCBW200.50	200	50	55.6	47	20	Ball bearing	500

Specification:

Type: PU on Iron Ball Bearing Wheels	Tread Color: Red
Wheel Diameter: 4 inch ~ 8 inch	Applicable Temperature: -25°C ~ 80°C
Core Material: Cast Iron	Load Capacity(kgs): 320 ~ 500
Hardness: 92° shore A	Bearing Type: Ball bearing



Model No.: CP120
Product name: Round Tread PU on Iron Wheels
Loading capacity: 320-680KGS
Wheel material: PU on Cast Iron



Round Tread PU on Iron Wheels



CP120RPCW

Model			Hub Length (mm)	Wheel Core(mm)	Bore Dia.(mm)		
CP120-RPCW100.50	100	50	50	40	17	Ball bearing	320
CP120-RPCW125.50	125	50	50	40	17	Ball bearing	400
CP120-RPCW150.50	150	50	50	40	17	Ball bearing	450
CP120-RPCW200.50	200	50	50	47	20	Ball bearing	680

Specification:

Type: Round Tread PU on Iron Wheels	Tread Color: Red
Wheel Diameter: 4 Inch ~ 8 Inch	Applicable Temperature: -25°C ~ 80°C
Core Material: Cast Iron	Load Capacity(kgs): 320 ~ 680
Hardness: 92° shore A	Bearing Type: Roller bearing



Model No.: CP121
Product name: PU on Aluminium Wheels
Loading capacity: 300-600KGS
Wheel material: PU on Aluminium



PU on Aluminium Wheels



CP121PAW

Model			Hub Length (mm)	Wheel Core(mm)	Bore Dia.(mm)		
CP121-PAW100.37	100	50	60	47	20	Ball bearing	300
CP121-PAW125.37	125	50	60	47	20	Ball bearing	350
CP121-PAW150.37	150	50	60	47	20	Ball bearing	400
CP121-PAW200.50	200	50	60	47	20	Ball bearing	500
CP121-PAW250.50	250	50	60	52	25	Ball bearing	600

Specification:

Type: PU on Aluminium Wheels	Tread Color: Yellow
Wheel Diameter: 4 Inch ~ 10 Inch	Applicable Temperature: -20°C ~ 80°C
Core Material: Aluminium	Load Capacity(kgs): 300 ~ 600
Hardness: 92° shore A	Bearing Type: Precision double ball bearing

Model No.: CP122
 Product name: Round Tread PU on Aluminium Wheels
 Loading capacity: 300~700KGS
 Wheel material: PU on Aluminium



Round Tread PU on Aluminium Wheels



CP122RPAW

Model			Hub Length (mm)	Wheel Core(mm)	Bore Dia.(mm)		
CP122-RPAW100.50	100	50	60	47	20	Ball bearing	300
CP122-RPAW125.50	125	50	60	47	20	Ball bearing	350
CP122-RPAW150.50	150	50	60	47	20	Ball bearing	500
CP122-RPAW200.50	200	50	60	47	20	Ball bearing	600
CP122-RPAW250.50	250	50	60	52	20	Ball bearing	700

Specification:

Type: Round Tread PU on Aluminium Wheels	Tread Color: Yellow
Wheel Diameter: 4 Inch ~ 10 Inch	Applicable Temperature: -25°C ~ 90°C
Core Material: Aluminium	Load Capacity(kgs): 300 ~ 700
Hardness: 92° shore A	Bearing Type: Precision double ball bearing

Model No.: CP123
 Product name: PU Mold on Nylon Wheels
 Loading capacity: 200~350KGS
 Wheel material: PU on Nylon



CP123PNW

Model			Hub Length (mm)	Wheel Core(mm)	Bore Dia.(mm)		
CP123-PNW100.32	100	32	40	30*9	10	Ball bearing	200
CP123-PNW125.35	125	35	51	35*11	15	Ball bearing	250
CP123-PNW150.38	250	38	51	35*11	15	Ball bearing	300
CP123-PNW200.45	200	45	53	40*12	17	Ball bearing	350

Specification:

Type: PU Mold on Nylon Wheels	Tread Color: Brown
Wheel Diameter: 3 Inch ~ 6 Inch	Applicable Temperature: -20°C ~ 80°C
Core Material: Nylon	Load Capacity(kgs): 200 ~ 350
Hardness: 93° shore A	Bearing Type: Precision double ball bearing

Model No.: CP153
 Product name: TPR on PP Wheels
 Loading capacity: 230~320KGS
 Wheel material: TPR on PP core



TPR on PP Wheels



CP153TPW-1 CP153TPW-2

Model			Hub Length (mm)	Wheel Core(mm)	Bore Dia.(mm)		
CP153-TPW100.50	100	50	60	47	20	Ball bearing	230
CP153-TPW125.50	125	50	60	47	20	Ball bearing	280
CP153-TPW150.50	150	50	60	47	20	Ball bearing	300
CP153-TPW200.50	200	50	60	47	20	Ball bearing	320

Specification:

Type: TPR on PP Wheels	Tread Color: Gray or Blue
Wheel Diameter: 4 inch ~ 8 inch	Applicable Temperature: -20°C ~ 80°C
Core Material: Plastic	Load Capacity(kgs): 230 ~ 320
Hardness: 92° shore A	Bearing Type: Precision double ball bearing

Model No.: CP154
 Product name: Elastic Rubber on Aluminium Wheels
 Loading capacity: 200~350KGS
 Wheel material: Elastic Rubber on Aluminium core



CP154RAW

Model			Hub Length (mm)	Wheel Core(mm)	Bore Dia.(mm)		
CP154RAW125.50	125	50	60	47	20	Ball bearing	200
CP154RAW150.50	150	50	60	47	20	Ball bearing	250
CP154RAW200.50	200	50	60	47	20	Ball bearing	300
CP154RAW250.50	250	50	60	47	20	Ball bearing	350

Specification:

Type: Elastic Rubber on Aluminium Wheels	Tread Color: Black
Wheel Diameter: 5 inch ~ 10 inch	Applicable Temperature: -30°C ~ 60°C
Core Material: Aluminium	Load Capacity(kgs): 200 ~ 350
Hardness: 70° shore A	Bearing Type: Precision double ball bearing



Rubber Wheels

Model No.: CP155
 Product name: Industrial Rubber on Steel Rim Wheels
 Loading capacity: 40~180KGS
 Wheel material: Elastic Rubber on Steel Rim



CP155IRSW

Model			Hub Length (mm)	Bore Dia.(mm)		
CP155-IRSW75.23	75	23	30	12	Roller bearing	40
CP155-IRSW85.24	85	24	30	12	Roller bearing	50
CP155-IRSW100.27	100	27	40	12	Roller bearing	60
CP155-IRSW125.34	125	34	40	15	Roller bearing	100
CP155-IRSW150.40	150	40	55	20	Roller bearing	110
CP155-IRSW160.40	160	40	55	20	Roller bearing	130
CP155-IRSW200.46	200	46	55	20	Roller bearing	150
CP155-IRSW250.50	250	50	55	20	Roller bearing	180

Specification:

Type: Industrial Rubber on Steel Rim Wheels	Tread Color: Black
Wheel Diameter: 3 Inch ~ 10 Inch	Applicable Temperature: -20°C ~ 50°C
Core Material: Steel Rim	Load Capacity(kgs): 200 ~ 350
Hardness: 70° shore A	Bearing Type: Roller bearing

Nylon Wheels



Model No.: CP175
 Product name: Light Duty White Nylon Wheels
 Loading capacity: 38~70KGS
 Wheel material: Nylon



CP175NW-1



CP175NW-2



CP175NW-3

Model			Hub Length (mm)	Bore Dia.(mm)		
CP175-NW50.19	50	19	23	10	Plain bearing	38
CP175-NW60.23	60	23	28	10	Plain bearing	50
CP175-NW80.24	80	24	29	10	Plain bearing	60
CP175-NW100.24	100	24	29	10	Plain bearing	70

Specification:

Type: Light Duty White Nylon Wheels	Tread Color: Black / White / Gray
Wheel Diameter: 2 Inch ~ 4 Inch	Applicable Temperature: -30°C ~ 90°C
Core Material: Nylon	Load Capacity(kgs): 38 ~ 70
Hardness: 75D ± 3	Bearing Type: Plain bearing



Nylon Wheels

Model No.: CP176

Product name: European Type Heavy Duty Nylon Wheels

Loading capacity: 300~600KGS

Wheel material: Nylon



CP176NW

Model			Hub Length (mm)	Bore Dia.(mm)		
CP176-NW80.38	80	38	48	15	Ball bearing	300
CP176-NW100.38	100	38	48	15	Ball bearing	400
CP176-NW125.38	125	38	48	15	Ball bearing	500
CP176-NW150.38	150	38	48	15	Ball bearing	600

Specification:

Type: European Type Heavy Duty Nylon Wheels	Tread Color: White
Wheel Diameter: 3 Inch ~ 6 Inch	Applicable Temperature: -30°C ~ 90°C
Core Material: Nylon	Load Capacity(kgs): 300 ~ 600
Hardness: 75D ± 3	Bearing Type: Ball bearing

Cast Iron Wheels



Model No.: CP196

Product name: Cast Iron Ball Bearing Wheels

Loading capacity: 500~1000KGS

Wheel material: Cast Iron



CP196CIBW-1 CP196CIBW-2

Model			Hub Length (mm)	Bore Dia.(mm)		
CP196-CIBW100.50	100	50	60	20	Roller bearing	500
CP196-CIBW125.50	125	50	60	20	Roller bearing	600
CP196-CIBW150.50	150	50	60	20	Roller bearing	700
CP196-CIBW200.50	200	50	60	20	Roller bearing	800
CP196-CIBW250.50	250	50	60	20	Roller bearing	1000

Specification:

Type: Cast Iron Ball Bearing Wheels	Tread Color: Silver Gray
Wheel Diameter: 4 Inch ~ 10 Inch	Applicable Temperature: -70°C ~ 400°C
Core Material: Cast Iron	Load Capacity(kgs): 500 ~ 1000
Hardness: >100D	Bearing Type: Ball bearing

Model No.: CP197

Product name: Cast Iron Roller Bearing Wheels

Loading capacity: 500~800KGS

Wheel material: Cast Iron



CP197CIRW

Model			Hub Length (mm)	Bore Dia.(mm)		
CP197-CIRW100.50	100	50	60	20	Roller bearing	500
CP197-CIRW125.50	125	50	60	20	Roller bearing	600
CP197-CIRW150.50	150	50	60	20	Roller bearing	700
CP197-CIRW200.50	200	50	60	20	Roller bearing	800

Specification:

Type: Cast Iron Roller Bearing Wheels	Tread Color: Silver Gray
Wheel Diameter: 4 Inch ~ 8 Inch	Applicable Temperature: -70°C ~ 400°C
Core Material: Cast Iron	Load Capacity(kgs): 500 ~ 800
Hardness: >100D	Bearing Type: Roller bearing

Model No.: CP198

Product name: Round Tread Cast Iron Wheels

Loading capacity: 80~100KGS

Wheel material: Cast Iron



CP198RCIW

Model			Hub Length (mm)	Bore Dia.(mm)		
CP198-RCIW50.22	50	22	25	6	Plain bearing	500
CP198-RCIW65.26	65	26	31	8	Plain bearing	600
CP198-RCIW75.32	75	32	40	10	Plain bearing	700
CP198-RCIW100.33	100	33	48	10	Plain bearing	800

Specification:

Type: Round Tread Cast Iron Wheels	Tread Color: Silver Gray
Wheel Diameter: 2 Inch ~ 4 Inch	Applicable Temperature: -70°C ~ 400°C
Core Material: Cast Iron	Load Capacity(kgs): 80 ~ 100
Hardness: >100D	Bearing Type: Plain bearing



Cast Iron Wheels

Model No.: CP199

Product name: V Groove Cast Iron Wheels

Loading capacity: 300~500KGS

Wheel material: Cast Iron



CP199VGCW

Model			Hub Length (mm)	Bore Dia.(mm)		
CP199-VGCW102.44	102	44	55.5	30.2	Ball bearing	300
CP199-VGCW127.44	127	44	55.5	30.2	Ball bearing	350
CP199-VGCW152.44	152	44	55.5	30.2	Ball bearing	400
CP199-VGCW202.44	202	44	55.5	30.2	Ball bearing	500

Specification:

Type: V Groove Cast Iron Wheels	Tread Color: Silver Gray
Wheel Diameter: 4 Inch ~ 8 Inch	Applicable Temperature: -70°C ~ 400°C
Core Material: Cast Iron	Load Capacity(kgs): 300 ~ 500
Hardness: >100D	Bearing Type: Ball bearing

PP Wheels



Model No.: CP220

Product name: Standard Industrial PP Single Wheels

Loading capacity: 40~150KGS

Wheel material: PP



CP220IPW

Model			Hub Length (mm)	Bore Dia.(mm)		
CP220-IPW75.23	75	23	30	12	Roller bearing	40
CP220-IPW100.27	100	27	40	12	Roller bearing	60
CP220-IPW125.34	125	34	40	15	Roller bearing	100
CP220-IPW160.40	160	40	55	20	Roller bearing	130
CP220-IPW200.46	200	46	55	20	Roller bearing	150

Specification:

Type: Standard Industrial PP Single Wheels	Tread Color: White
Wheel Diameter: 3 inch ~ 8 Inch	Applicable Temperature: -20°C ~ 80°C
Core Material: PP	Load Capacity(kgs): 40 ~ 150
Hardness: 75D	Bearing Type: Roller bearing



Model No.: CP221
Product name: Black Round Tread PP Wheels
Loading capacity: 70~100KGS
Wheel material: PP



CP221RPW

Model			Hub Length (mm)	Bore Dia.(mm)		
CP221-RPW50.23	50	23	25	6	Plain bearing	70
CP221-RPW63.22	63	22	32	10	Plain bearing	75
CP221-RPW74.31	74	31	39	10	Plain bearing	80
CP221-RPW100.32	100	32	47	11	Plain bearing	100

Specification:

Type: Black Round Tread PP Wheels	Tread Color: Black
Wheel Diameter: 2 Inch ~ 4 Inch	Applicable Temperature: -20°C ~ 80°C
Core Material: PP	Load Capacity(kgs): 70 ~ 100
Hardness: 75D	Bearing Type: Plain bearing



Model No.: CP222
Product name: Heavy Duty PP Wheels
Loading capacity: 200~350KGS
Wheel material: PP



CP222HPW

Model			Hub Length (mm)	Bore Dia.(mm)		
CP222-HPW100.50	100	50	60	19	Roller bearing	200
CP222-HPW125.50	125	50	60	19	Roller bearing	220
CP222-HPW150.50	150	50	60	19	Roller bearing	300
CP222-HPW200.50	200	50	60	19	Roller bearing	350

Specification:

Type: Heavy Duty PP Wheels	Tread Color: Black
Wheel Diameter: 4 Inch ~ 8 Inch	Applicable Temperature: -20°C ~ 80°C
Core Material: High Quality PP	Load Capacity(kgs): 200 ~ 350
Hardness: 75D	Bearing Type: Steel Roller bearing



Model No.: CP242
Product name: Black Baking Oven Phenolic Wheels
Loading capacity: 200~500KGS
Wheel material: Phenol aldehyde series



CP242PHW

Model			Hub Length (mm)	Bore Dia.(mm)		
CP242-PHW100.50	100	50	60	19	Roller bearing	200
CP242-PHW125.50	125	50	60	19	Roller bearing	300
CP242-PHW150.50	150	50	60	19	Roller bearing	400
CP242-PHW200.50	200	50	60	19	Roller bearing	500

Specification:

Type: Black Baking Oven Phenolic Wheels	Tread Color: Black
Wheel Diameter: 4 Inch ~ 8 Inch	Applicable Temperature: 0°C ~ 300°C
Core Material: Phenol aldehyde series	Load Capacity(kgs): 200 ~ 500
Hardness: 136 ± 60N	Bearing Type: Steel roller bearing



Model No.: CP243
Product name: High Temperature Resistance Phenolic Wheels
Loading capacity: 370~450KGS
Wheel material: Phenol aldehyde material



CP243PHW

Model			Hub Length (mm)	Bore Dia.(mm)		
CP243-PHW100.50	100	50	60	12.7	Roller bearing	370
CP243-PHW125.50	125	50	60	12.7	Roller bearing	400
CP243-PHW150.50	150	50	60	12.7	Roller bearing	420
CP243-PHW200.50	200	50	60	12.7	Roller bearing	450

Specification:

Type: High Temperature Resistance Phenolic Wheels	Tread Color: Reddish Brown
Wheel Diameter: 4 Inch ~ 8 Inch	Applicable Temperature: 0°C ~ 300°C
Core Material: Phenol aldehyde material	Load Capacity(kgs): 370 ~ 450
Hardness: 136 ± 60N	Bearing Type: Steel roller bearing



Fork Lift Truck Wheels

Model No.: CP253

Product name: Electric Forklift Truck Wheels

Loading capacity: 450~2500KGS

Wheel material: PU on cast iron

LINDE FORKLIFT WHEELS SERIES



CP253EFLW-1 CP253EFLW-2 CP253EFLW-3 CP253EFLW-4 CP253EFLW-5

We can provide Electric Forklift Wheels for the world famous brand such as LINDE, TOYOTA, CROWN, HYSTER, NICHYU, MAXIMAL AND HYUNDAI ETC. We could also customize your needs based on your brand fitting wheels.

Model	Metric specification	Linde original part No	Recommended part number of outsourcing parts	Model matching and use		Icons
				Models	use	
CP253-EFLW-DL085-5	85x80 / 85-55 / 12	0039933803	LXEV4-0039933803	T20ap(1158series) / T30	Loading wheel	6006
				T20sp / ap(131series)		
				T20(1151 / 1152series)		
CP253-EFLW-DL085-6	85x85 / 90-55 / 12	0039903513	LXEV4-0039903513	L14AP1168 / 372	Loading wheel	6006
CP253-EFLW-DL085-10	85x60 / 65-55 / 12	0039903512	LXEV4-0039903512	L14AP1168 / 372	Loading wheel	6006
CP253-EFLW-DL085-15	85x77 / 82-55 / 12	0009933902	LXEV4-0009933902	L10 / L12new(1169)	Loading wheel	6006
CP253-EFLW-DL100-2	100x40-35 / 15	0039903519	LXEV4-0039903519	T30	Balance wheel	6202
				T20ap(1158series)		
CP253-EFLW-DL100-9	100x45-42 / 12					
CP253-EFLW-DL125-4	125x60-47 / 20	0009933803	LXEV4-0009933803	T20sp / ap(131series)	Balance wheel	6204
CP253-EFLW-DL125-7	125x40-35 / 15	0009933864	LXEV4-0009933864	T20(1151 / 1152series)	Balance wheel	6202
CP253-EFLW-DL140-1	140x50-55 / 12	0039933811	LXEV4-0039933811	4590 / 4589 / 4587-0189	Balance wheel	6006
CP253-EFLW-DL140-6	140x55(60)-47 / 20	0009934020	LXEV4-0009934020	L14AP1168 / 372	Balance wheel	6204
				L10 / L12 new(1169)		
CP253-EFLW-DL150-1	150x48 / 60-55 / 12	0039903515	LXEV4-0039903515	L14AP1168 / 372	Balance wheel	6006
CP253-EFLW-DL230-1F	230x75-170 / 45	0009903819	LXEV4-0009903819	T20(1151 / 1152series)	Drive wheel	
				L10 / L12 new(1169)		
CP253-EFLW-DL230-3	230x90(5holes)	0039933826	LXEV4-00039933826	L14AP1168 / 372	Drive wheel	
CP253-EFLW-DL230-2	230x90(4holes)	0039902305	LXEV4-0039902305	L12 / T20	Drive wheel	
CP253-EFLW-DL254-4	254x102-80	0039902311	LXEV4-0039902311	T20ap(1158series) / T30	Drive wheel	
				T20sp / ap(131series)		
CP52-EFLW-DL285-1A	285x100-68	0029902329	LXEV4-0029902329	R14-16	Loading wheel	
CP253-EFLW-DL343-1	343x135-90	0029903814	LXEV4-0029903814	R14-16 R20	Drive wheel	
CP253-EFLW-DL343-2	343x135-80	9815000599	LXEV4-9815000599	R14-16	Drive wheel	
CP253-EFLW-DL350-1	350x100	0029902330	LXEV4-0029902330	R20	Loading wheel	
CP253-EFLW-200-2	200x103x159			MT15(1133)	Drive wheel	

Specification:

Type: Electric Forklift Truck Wheels	Tread Color: Yellow
Wheel Diameter: 3.5 inch ~ 14 inch	Applicable Temperature: -30°C ~ 80°C
Core Material: Cast Iron	Load Capacity(kgs): 450 ~ 2500
Hardness: 98 shore A	Bearing Type: Refer to data sheet



Model No.: CP254

Product name: PU Pallet Jack Steering Wheels

Loading capacity: 400~850KGS

Wheel material: PU on Cast Iron



PU on Iron with precision ball bearing



CP254PSW

Model	Icons 1	Icons 2	Hub Length (mm)	Wheel Core(mm)	Bore Dia.(mm)	Icons 3	Icons 4
CP254-PSW150.50-B4	150	50	50	47*14	20	Ball bearing	400
CP254-PSW160.50-B4	160	50	50	47*14	20	Ball bearing	450
CP254-PSW180.50-B4	180	50	50	47*14	20	Ball bearing	500
CP254-PSW180.60-B4	180	60	60	47*14	20	Ball bearing	550
CP254-PSW180.70-B4	180	70	70	47*14	20	Ball bearing	600
CP254-PSW200.50-B4	200	50	50	47*14	20	Ball bearing	550
CP254-PSW200.50-B5	200	50	50	52*15	25	Ball bearing	850

Specification:

Type: PU Pallet Jack Steering Wheels	Tread Color: Red
Wheel Diameter: 6 inch ~ 8 inch	Applicable Temperature: -25°C ~ 80°C
Core Material: Cast Iron	Load Capacity(kgs): 400 ~ 850
Hardness: 92° shore A	Bearing Type: Ball bearing

Model No.: CP255
 Product name: Nylon Pallet Truck Rollers
 Loading capacity: 610~1050KGS
 Wheel material: Nylon



	Model			Hub Length (mm)	Bore Dia.(mm)		
	CP255-NRW74.70	74	70	70	20	Ball bearing	610
	CP255-NRW74.93	74	93	93	20	Ball bearing	810
	CP255-NRW78.70	78	70	70	20	Ball bearing	610
	CP255-NRW78.100	18	100	100	20	Ball bearing	910
	CP255-NRW80.60	80	60	60	20	Ball bearing	460
	CP255-NRW80.70	80	70	70	20	Ball bearing	490
	CP255-NRW80.80	80	80	80	20	Ball bearing	490
	CP255-NRW80.90	80	90	90	20	Ball bearing	650
	CP255-NRW80.100	80	100	100	20	Ball bearing	700
	CP255-NRW82.60	82	60	60	20	Ball bearing	710
	CP255-NRW82.65	82	65	65	20	Ball bearing	760
	CP255-NRW82.70	82	70	70	20	Ball bearing	790
	CP255-NRW82.92	82	92	92	20	Ball bearing	810
	CP255-NRW82.100	82	100	100	20	Ball bearing	960
	CP255-NRW85.75	85	75	75	20	Ball bearing	960
	CP255-NRW85.90	85	90	90	20	Ball bearing	960
	CP255-NRW85.100	85	100	100	20	Ball bearing	1050

Specification:

Type: Nylon Pallet Truck Rollers	Tread Color: White
Wheel Diameter: 3 inch ~ 3.5 inch	Applicable Temperature: -30°C ~ 90°C
Core Material: Nylon	Load Capacity(kgs): 610 ~ 1050
Hardness: 75D ± 3	Bearing Type: Ball bearing

Model No.: CP256
 Product name: PU Steel Hand Pallet Truck Rollers
 Loading capacity: 180~900KGS
 Wheel material: PU



	Model		Axel Bore Φ(mm)	Hub Length (mm)	Wheel core(mm)		
	CP256-UR60.35-B1	60*35	15	35	32*9	6002ZZ	180
	CP256-UR60.60-B1	60*60	10	56	30*11	6200ZZ	320
	CP256-UR75.40-B4	75*40	20	40	47*14	6204ZZ	270
	CP256-UR75.62-B4	75*62	20	62	47*14	6204ZZ	410
	CP256-UR75.75-B4	75*75	20	75	47*14	6204ZZ	500
	CP256-UR75.79-B4	75*95	20	95	47*14	6204ZZ	640
	CP256-UR80.30-B2	80*30	12	27	32*12	6201ZZ	210
	CP256-UR80.40-B4	80*40	20	40	47*14	6204ZZ	280
	CP256-UR80.54-B4	80*54	20	54	47*14	6204ZZ	380
	CP256-UR80.56-B4	80*56	20	56	47*14	6204ZZ	400
	CP256-UR80.60-B4	80*60	20	66	47*14	6204ZZ	420
	CP256-UR80.62-B4	80*62	20	54	47*14	6204ZZ	440
	CP256-UR80.70-B4	80*70	20	70	47*14	6204ZZ	500
	CP256-UR80.74-B3	80*74	20	68	42*14	6004ZZ	530
	CP256-UR80.80-B4	80*80	20	80	47*14	6204ZZ	570
	CP256-UR80.95-B3	80*95	20	89	42*14	6004ZZ	680
	CP256-UR82.50-B4	82*50	20	52	47*13	6204ZZ	360
	CP256-UR82.60-B3	82*60	20	60	42*14	6004ZZ	440
	CP256-UR82.60-B4	82*60	25	60	47*14	6005ZZ	440
		CP256-UR82.62-B4	82*62	20	64	47*13	6204ZZ
CP256-UR82.65-B4		82*65	20	65	47*14	6204ZZ	470
CP256-UR82.70-B4		82*70	20	70	47*14	6204ZZ	510
CP256-UR82.80-B4		82*80	20	80	47*14	6204ZZ	580
CP256-UR82.90-B4		82*90	20	90	47*14	6204ZZ	660
CP256-UR82.100-B4		82*100	20	100	47*14	6204ZZ	730
CP256-UR85.70-B4		85*70	20	70	47*14	6204ZZ	530
CP256-UR85.80-B4		85*80	25	80	47*14	6005ZZ	530
CP256-UR85.90-B4		85*90	20	90	47*14	6204ZZ	680
CP256-UR85.100-B4		85*100	25	100	47*14	6005ZZ	760
CP256-UR85.120-B4	85*120	25	124	47*14	6005ZZ	900	

Specification:

Type: PU Steel Hand Pallet Truck Rollers	Tread Color: Yellow / Brown / Red
Wheel Diameter: 2.4 inch ~ 3.5 inch	Applicable Temperature: -25°C ~ 80°C
Core Material: Steel	Load Capacity(kgs): 180 ~ 900
Hardness: 92° Shore A	Bearing Type: Ball bearing



Fork Lift Truck Wheels

Model No.: CP257
 Product name: Nylon Pallet Truck Steering Wheels
 Loading capacity: 180~250KGS
 Wheel material: Nylon



CP257NSW

Model		Axel Bore Φ (mm)	Hub Length (mm)	Wheel core(mm)		
CP257-NSW180.50	180*50	20	50	47*14	Ball Bearing	180
CP257-NSW200.50	200*50	20	50	47*14	Ball Bearing	200
CP257-NSW250.50	250*50	25	50	47*14	Ball Bearing	250

Specification:

Type: Nylon Pallet Truck Steering Wheels	Tread Color: White
Wheel Diameter: 7 inch ~ 10 inch	Applicable Temperature: -25℃ ~ 85℃
Core Material: Nylon	Load Capacity(kgs): 180 ~ 250
Hardness: Very hard 75D ± 3	Bearing Type: Ball bearing

Hand Trolleys



Model No.: CP277
 Product name: High Grade Plastic Foldable Hand Carts
 Loading capacity: 150~500KGS
 Wheel material: pp



	Model	Platform Size (mm)	Wheel Install height(mm)			
CP277PFC	CP277-PFC700.500	700*500	150	820	100	150
	CP277-PFC900.600	900*600	200	860	125	300
	CP277-PFC1050.630	1050*630	200	860	125	500

Specification:

Type: High Grade Plastic Foldable Hand Carts	Color: Green(Can be customized)
Wheel Diameter: 4 inch ~ 5 inch	Applicable Temperature: -20℃ ~ 60℃
Core Material: PP	Load Capacity(kgs): 150 ~ 500
Hardness: Level: Very hard 75D	Optional Wheels: PU / TPR / PVC / PP / NYLON / RUBBER wheels

Model No.: CP278
 Product name: Stainless Steel Foldable Hand Carts
 Loading capacity: 150~500KGS
 Wheel material: Stainless steel



	Model	Platform Size (mm)	Wheel Install height(mm)			
CP278SFC	CP278-SFC700.460	700*460	150	850	100	150
	CP278-SFC900.600	900*600	200	900	125	300
	CP278-SFC1200.660	1200*660	200	900	125	500

Specification:

Type: Stainless Steel Foldable Hand Carts	Color: Silver
Wheel Diameter: 4 inch ~ 5 inch	Applicable Temperature: -70℃ ~ 400℃
Material: Stainless steel	Load Capacity(kgs): 150 ~ 500
Hardness: Level: Very hard > 100D	Optional Wheels: PU / TPR / PVC / PP / NYLON / RUBBER / Cast Iron wheels



Hand Trolleys

Model No.: CP279

Product name: Aluminium Platform Foldable Hand Carts

Loading capacity: 150KGS

Wheel material: Aluminium



CP279AFC

Model	Platform Size (mm)	Wheel Install height(mm)			
CP279-AFC740.480	740*480	150	900	100	150

Specification:

Type: Aluminium Platform Foldable Hand Carts	Color: Silver
Wheel Diameter: 4 inch	Applicable Temperature: -50°C ~ 100°C
Material: Steel and aluminium	Load Capacity(kgs): 150
Optional Wheels: PU / TPR / PVC / PP / NYLON / RUBBER / Cast Iron wheels	

Model No.: CP280

Product name: Blue Steel Tube Foldable Hand Carts

Loading capacity: 150KGS

Wheel material: Steel



CP280STFC

Model	Platform Size (mm)	Wheel Install height(mm)			
CP280-STFC750.500	750*500	130	890	100	150
CP280-STFC900.600	900*600	160	890	125	300
CP280-STFC1000.900	1000*900	160	890	125	400

Specification:

Type: Blue Steel Tube Foldable Hand Carts	Color: Blue
Wheel Diameter: 4inch ~ 5inch	Applicable Temperature: -70°C ~ 400°C
Material: Steel	Load Capacity(kgs): 150
Optional Wheels: PU / TPR / PVC / PP / NYLON / RUBBER / Cast Iron wheels	



Model No.: CP281

Product name: Steel Mesh Tool Carts

Loading capacity: 300KGS

Wheel material: Steel



CP281SMC

Model	Platform Size (mm)	Wheel Install height(mm)			
CP281-SMC900.600	900*600	215	715	125	300

Specification:

Type: Steel Mesh Tool Carts	Color: Blue
Wheel Diameter: 5inch ~ 6inch	Applicable Temperature: -70°C ~ 400°C
Material: Steel	Load Capacity(kgs): 300
Optional Wheels: PU / TPR / PVC / PP / NYLON / RUBBER / Cast Iron wheels	

Model No.: CP282




Product name: Stainless Steel Foldable Luggage Hand Trolleys

Loading capacity: 100KGS

Wheel material: Stainless Steel



CP282SFLC

Model	Broadening Size(mm)	Rack Size (mm)	Wheel Install height(mm)			
CP282-SFLC440.460	440*460	420*360	NA	960	30 / 125	100

Specification:

Type: Stainless Steel Foldable Luggage Hand Trolleys	Color: Blue
Wheel Diameter: 1.5inch ~ 5 inch	Applicable Temperature: -70°C ~ 400°C
Material: Stainless Steel	Load Capacity(kgs): 100
Optional Wheels: PU / TPR / PVC / PP / NYLON / RUBBER / Cast Iron wheels	

Model No.: CP283

Product name: Multifunctional Aluminium Alloy Stair Hand Truck

Loading capacity: 300KGS

Wheel material: Aluminium Alloy With Steel



CP283AST

Model	Board Size(mm)	Fodable size(mm)	Broadening Size(mm)	Wheel Install height(mm)			
CP283-AST1180.500	1180*500	460*520*1310	1180*520*1030	NA	1310	30 / 125	250 / 300

Specification:

Type: Multifunctional Aluminium Alloy Stair Hand Truck	Color: Silver
Wheel Diameter: 10 inch	Applicable Temperature: -60°C ~ 100°C
Material: Aluminium Alloy T5, steel A3	Load Capacity(kgs): 300
Optional Wheels: PU / TPR / PVC / PP / NYLON / RUBBER / Cast Iron wheels	

Model No.: CP284

Product name: Aluminium Foldable Stair Hand Truck

Loading capacity: 70KGS

Wheel material: Aluminium With Steel



CP284AFSC-1 CP284AFSC-2

Model	Board Size(mm)	Fodable size(mm)	Broadening Size(mm)	Wheel Install height(mm)			
CP284-AFSC390.280	390*280	640*394*47	1000*394*406	NA	1000	125	70

Specification:

Type: Aluminium Foldable Stair Hand Truck	Color: Silver
Wheel Diameter: 5 inch	Applicable Temperature: -60°C ~ 100°C
Material: Aluminium with steel	Load Capacity(kgs): 70
Optional Wheels: PU / TPR / PVC / PP / NYLON / RUBBER / Cast Iron wheels	

Model No.: CP285

Product name: Triangular wheel Suitcase Stair Hand Truck

Loading capacity: 50KGS

Wheel material: Steel with plastic



CP285-1



CP285-2

Model	Board Size (mm)	Broadening Size(mm)		Volume.(L)	
CP285-TFSC350.200	350*200	970*350*430	970	50	50

Specification:

Type: Triangular wheel Suitcase Stair Hand Truck	Color: Blue
Wheel Diameter: Multiple	Applicable Temperature: -60°C ~ 100°C
Material: Steel with plastic	Load Capacity(kgs): 50
Optional Wheels: PU / TPR / PVC / PP / NYLON / RUBBER / Cast Iron wheels	

Model No.: CP286

Product name: Triangular wheel Shopping Stair Hand Truck

Loading capacity: 50KGS

Wheel material: Aluminium With Steel



CP286-1



CP286-2

Model	Inner Size (mm)	Fodable size(mm)	Broadening Size(mm)	Wheel Install height(mm)		
CP286-TFSC290.300	290*300*370	930*420*190	930*420*420	NA	960	50

Specification:

Type: Triangular wheel Shopping Stair Hand Truck	Color: Silver
Wheel Diameter: Multiple	Applicable Temperature: -60°C ~ 100°C
Material: Aluminium with steel	Load Capacity(kgs): 50
Optional Wheels: PU / TPR / PVC / PP / NYLON / RUBBER / Cast Iron wheels	



Floor Locks

Model No.: CP301

Product name: Japan Type Floor Locks

Loading capacity: 260-500KGS

Wheel material: Steel



	Model	Size(inch)	Extended Height (mm)	Retracted height (mm)	Top plate Size(mm)	Top plate hole spacing (mm)	Top plate hole size (mm)	
	CP301FLJ-4	4	150	135	120*120	85*85 / 100*100	11	260
	CP301FLJ-5	5	180	150	120*120	85*85 / 100*100	11	290
	CP301FLJ-6	6	210	170	120*120	85*85 / 100*100	11	360
	CP301FLJ-8	8	259	217	120*120	85*85 / 100*100	11	500

Specification:

Type: Japan Type Floor Locks	Color: Silver with green
Size: 4, 5, 6, 8 inch	Applicable Temperature: -60°C ~ 100°C
Material: Steel with rubber base	Load Capacity(kgs): 260 - 500

Model No.: CP302

Product name: American Type Floor Locks

Loading capacity: 200-250KGS

Wheel material: Steel



	Model	Size(inch)	Extended Height (mm)	Retracted height (mm)	Top plate Size(mm)	Top plate hole spacing (mm)	Top plate hole size (mm)	
	CP302FLA-4	4	152	128	115*100	85*75	6	200
	CP302FLA-5	5	180	158	115*100	85*75	6	200
	CP302FLA-6	6	195	170	115*100	85*75	6	250
	CP302FLA-8	8	242	218	115*100	85*75	6	250

Specification:

Type: American Type Floor Locks	Color: Silver with green
Size: 4, 5, 6, 8 inch	Applicable Temperature: -60°C ~ 100°C
Material: Steel with rubber base	Load Capacity(kgs): 200 - 250

Medium Heavy Duty Forks



Model No.: CP310

Product name: Light Duty Forks for Casters

Optional Wheel: PP wheel, nylon wheel, TPR Wheel

Loading capacity: 40-60KGS

Housing: Made of pressed steel, zinc plated, double ballrace swivel head

Material: Steel



Swivel Caster



Model	Fork size		Total Height with wheel (mm)			Hole Spacing(mm)		
CP310ZS-LF-1.5	1.5 inch	19	60	25	54*44*2	40 / 30*40 / 30	6.2	40
CP310ZS-LF-2	2 inch	20	70	25	54*44*2	40 / 30*40 / 30	6.2	50
CP310ZS-LF-2.5	2.5 inch	20	85	25	54*44*2	40 / 30*40 / 30	6.2	60

Rigid Caster



Model	Fork size		Total Height with wheel (mm)			Hole Spacing(mm)		
CP310ZR-LF-1.5	1.5 inch	NA	60	25	54*44*2	40 / 30*40 / 30	6.2	40
CP310ZR-LF-2	2 inch	NA	70	25	54*44*2	40 / 30*40 / 30	6.2	50
CP310ZR-LF-2.5	2.5 inch	NA	85	25	54*44*2	40 / 30*40 / 30	6.2	60

Double Brake Caster



Model	Fork size		Total Height with wheel (mm)			Hole Spacing(mm)		
CP310ZT-LF-1.5	1.5 inch	19	60	25	54*44*2	40 / 30*40 / 30	6.2	40
CP310ZT-LF-2	2 inch	20	70	25	54*44*2	40 / 30*40 / 30	6.2	50
CP310ZT-LF-2.5	2.5 inch	20	85	25	54*44*2	40 / 30*40 / 30	6.2	60

Optional Wheels



Specification:

Type: Light Duty Forks for Casters	
Fork size(mm): 1.5inch / 2inch / 2.5inch	Surface Treatment: Zinc plated
Tread Material: PU	Applicable Temperature: -30°C ~ 80°C
Top plate thickness(mm): 2	Load Capacity(kgs): 40 ~ 60
Housing Thickness(mm): 2	Swivel Bearing Type: Ball bearings

Model No.: CP311

Product name: Light Medium Duty Forks for Casters

Optional Wheel: PP wheel, nylon wheel, TPR Wheel

Loading capacity: 70-90KGS

Housing: Made of pressed steel, zinc plated, double ball-race swivel head

Material: Steel



Swivel Caster



Model	Fork size		Total Height with wheel (mm)			Hole Spacing(mm)		
CP311ZS-LF-2.5	2.5 inch	34	91	33	70*58*2.5	55.5 / 54.5*44.2 / 37.2	8.2	70
CP311ZS-LF-3	3 inch	30	104	33	70*58*2.5	55.5 / 54.5*44.2 / 37.2	8.2	80
CP311ZS-LF-4	4 inch	25	126	33	70*58*2.5	55.5 / 54.5*44.2 / 37.2	8.2	90

Rigid Caster



Model	Fork size		Total Height with wheel (mm)			Hole Spacing(mm)		
CP311ZR-LF-2.5	2.5 inch	NA	91	33	70*58*2.5	55.5 / 54.5*44.2 / 37.2	8.2	70
CP311ZR-LF-3	3 inch	NA	104	33	70*58*2.5	55.5 / 54.5*44.2 / 37.2	8.2	80
CP311ZR-LF-4	4 inch	NA	126	33	70*58*2.5	55.5 / 54.5*44.2 / 37.2	8.2	90

Double Brake Caster



Model	Fork size		Total Height with wheel (mm)			Hole Spacing(mm)		
CP311ZT-LF-2.5	2.5 inch	34	91	33	70*58*2.5	55.5 / 54.5*44.2 / 37.2	8.2	70
CP311ZT-LF-3	3 inch	30	104	33	70*58*2.5	55.5 / 54.5*44.2 / 37.2	8.2	80
CP311ZT-LF-4	4 inch	25	126	33	70*58*2.5	55.5 / 54.5*44.2 / 37.2	8.2	90

Bolt Hole Swivel



Model	Fork size		Total Height with wheel (mm)			
CP311ZHS-LF-2.5	2.5 inch	34	87	33	10.2	70
CP311ZHS-LF-3	3 inch	30	101	33	10.2	80
CP311ZHS-LF-4	4 inch	25	122	33	10.2	90



Model	Fork size		Total Height with wheel (mm)			
CP311ZHT-LF-2.5	2.5 inch	34	87	33	10.2	70
CP311ZHT-LF-3	3 inch	30	101	33	10.2	80
CP311ZHT-LF-4	4 inch	25	122	33	10.2	90

Optional Wheels



Specification:

Type: Light Medium Duty Forks for Casters	
Fork size(mm): 2.5inch / 3inch / 4inch	Surface Treatment: Zinc plated
Tread Material: PU	Applicable Temperature: -30°C ~ 80°C
Top plate thickness(mm): 2 / 2.5	Load Capacity(kgs): 70 ~ 90
Housing Thickness(mm): 2	Swivel Bearing Type: Ball bearings

Model No.: CP312

Product name: Medium Duty Forks for Casters

Optional Wheel: PP wheel, nylon wheel, TPR Wheel

Loading capacity: 120~180KGS

Housing: Made of pressed steel, zinc plated, double ball-race swivel head

Material: Steel



Swivel Caster



Model	Fork size		Total Height with wheel (mm)			Hole Spacing(mm)	
CP312ZS-LF-3	3 inch	40	108	41	95*64*4	71 / 78*45	8.5 120
CP312ZS-LF-4	4 inch	36	133	41	95*64*4	71 / 78*45	8.5 170
CP312ZS-LF-5	5 inch	36	160	41	95*64*4	71 / 78*45	8.5 180

Rigid Caster



Model	Fork size		Total Height with wheel (mm)			Hole Spacing(mm)	
CP312ZR-LF-3	3 inch	NA	108	41	95*64*4	71 / 78*45	8.5 120
CP312ZR-LF-4	4 inch	NA	133	41	95*64*4	71 / 78*45	8.5 170
CP312ZR-LF-5	5 inch	NA	160	41	95*64*4	71 / 78*45	8.5 180

Double Brake Caster



Model	Fork size		Total Height with wheel (mm)			Hole Spacing(mm)		
CP312ZT-LF-3	3 inch	40	108	41	95*64*4	71 / 78*45	8.5	120
CP312ZT-LF-4	4 inch	36	133	41	95*64*4	71 / 78*45	8.5	170
CP312ZT-LF-5	5 inch	36	160	41	95*64*4	71 / 78*45	8.5	180

Optional Wheels



Specification:

Type: Medium Duty Forks for Casters	
Fork size(mm): 3inch / 4inch / 5inch	Surface Treatment: Zinc plated
Tread Material: PU	Applicable Temperature: -30°C ~ 80°C
Top plate thickness(mm): 3 / 4	Load Capacity(kgs): 120 ~ 180
Housing Thickness(mm): 2.5 / 3	Swivel Bearing Type: Ball bearings

Model No.: CP313

Product name: Industrial Heavy Duty Forks for Casters

Optional Wheel: PU wheel, PP wheel, nylon wheel, TPR Wheel

Loading capacity: 400~500KGS

Housing: Made of pressed steel, zinc plated, double ball-race swivel head

Material: Steel



Swivel Caster



Model	Fork size		Total Height with wheel (mm)			Hole Spacing(mm)		
CP313ZS-LF-4	4 inch	30	143	61	116*100*6	92 / 77*76 / 67	11	400
CP313ZS-LF-5	5 inch	38	164	61	116*100*6	92 / 77*76 / 67	11	420
CP313ZS-LF-6	6 inch	40	188	61	116*100*6	92 / 77*76 / 67	11	450
CP313ZS-LF-8	8 inch	58	236	61	116*100*6	92 / 77*76 / 67	11	500

Rigid Caster



Model	Fork size		Total Height with wheel (mm)			Hole Spacing(mm)		
CP313ZR-LF-4	4 inch	NA	143	61	116*100*6	92 / 77*76 / 67	11	400
CP313ZR-LF-5	5 inch	NA	164	61	116*100*6	92 / 77*76 / 67	11	420
CP313ZR-LF-6	6 inch	NA	188	61	116*100*6	92 / 77*76 / 67	11	450
CP313ZR-LF-8	8 inch	NA	236	61	116*100*6	92 / 77*76 / 67	11	500



Medium Heavy Duty Forks

Double Brake Caster



Model	Fork size		Total Height with wheel (mm)			Hole Spacing(mm)		
CP313ZT-LF-4	4 inch	30	143	61	116*100*6	92 / 77*76 / 67	11	400
CP313ZT-LF-5	5 inch	38	164	61	116*100*6	92 / 77*76 / 67	11	420
CP313ZT-LF-6	6 inch	40	188	61	116*100*6	92 / 77*76 / 67	11	450
CP313ZT-LF-8	8 inch	58	236	61	116*100*6	92 / 77*76 / 67	11	500

Optional Wheels



Specification:

Type: Industrial Heavy Duty Forks for Casters

Fork size(mm): 4inch / 5inch / 6inch / 8inch

Tread Material: PU

Top plate thickness(mm): 6

Housing Thickness(mm): 6

Surface Treatment: Zinc plated

Applicable Temperature: -30°C ~ 80°C

Load Capacity(kgs): 400 ~ 500

Swivel Bearing Type: Ball bearings

Leveling Feet



Model No.: CP324

Product name: Fixed Leveling Feet

Feet size: M10 / M16 / M20 / M30...



Model: CP324KVF-16100-80

Surface Treatment: Nickel plated / galvanized

Material: Screw is made of carbon steel, chassis is made of reinforced nylon (PA6)

Artwork: The screw is machined, connected by a circlip, and molded into a chassis

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP324KVF-16100-80	M16	100	80



Model: CP324KVF-1038-80

Surface Treatment: Galvanized

Material: Screw is made of carbon steel, chassis is made of reinforced nylon (PA6)

Artwork: The screw is made of outer hexagon, fixed by nut, and molded by chassis

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP324KVF-1038-80	M10	38	80



Model: CP324KVF-20100-80

Surface Treatment: Nickel plated

Material: Reinforced nylon (PA6) is used as the chassis, carbon steel is used as the screw

Artwork: The screw is machined, connected by a circlip, and molded into a chassis

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP324KVF-20100-80	M20	100	80



Model: CP324KVF-20150-100
 Surface Treatment: Galvanized
 Material: Reinforced nylon (PA6) is used as the chassis, the screw is made of carbon steel
 Artwork: The screw is machined, connected by a circlip, and molded into a chassis

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP324KVF-20150-100	M20	150	100



Model: CP324KVF-10100-30
 Surface Treatment: Galvanized
 Material: Reinforced nylon (PA6) is used as the chassis, the screw is made of carbon steel
 Artwork: The screw is made of outer hexagon, fixed by rivets, and injected by chassis

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP324KVF-10100-30	M10	100	30



Model: CP324KVF-1250-50
 Surface Treatment: Galvanized
 Material: Reinforced nylon (PA6) is used as the chassis, the screw is made of carbon steel
 Artwork: The screw is made of outer hexagon and non-hexagon, injection molding

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP324KVF-1250-50	M12	50	50



Model: CP324KVF-1040-30
 Surface Treatment: Galvanized
 Material: Reinforced nylon (PA6) is used as the chassis, the screw is made of carbon steel
 Artwork: The screw is hexagonal, connected by rivets, and the chassis is made of injection molding

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP324KVF-1040-30	M10	40	30



Model: CP324KVF-1450-40
 Surface Treatment: Galvanized
 Material: Reinforced nylon (PA6) is used as the chassis, the screw is made of carbon steel
 Artwork: The screw is made of outer hexagon, injection molding

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP324KVF-1450-40	M14	40	40

Specification:

Type: Fixed Leveling Feet

Feet size: M10 / M16 / M20 / M30...

Surface Treatment: Nickel plated / galvanized / Chrome / blackened / painted, etc; 304 or 316 stainless steel is also available

Material: Screw is made of carbon steel, chassis: rubber / reinforced nylon (PA6)

Applicable Temperature: -60°C ~ 80°C

Artwork: Screw and chassis are machined and connected by circlip

Model No.: CP325
 Product name: Steel Fixed Leveling Feet
 Feet size: M10 / M16 / M20 / M30...



Model: CP325KSVF-30100-100
 Surface Treatment: Nickel plated / galvanized zinc
 Material: The screw and chassis are made of 304 stainless steel, the chassis is made of polyurethane, or all carbon steel
 Artwork: Screw and chassis are machined and connected with small screws

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP325KSVF-30100-100	M30	100	100



Model: CP325KCVF-20150-100
 Surface Treatment: Nickel plated
 Material: The screw and chassis are all made of carbon steel
 Artwork: Screw and chassis are machined and connected by circlip

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP325KCVF-20150-100	M20	150	100



Model: CP325KCVF-20100-60
 Surface Treatment: Galvanized zinc
 Material: Screw and chassis are all made of carbon steel
 Artwork: Screw and chassis are machined and connected by circlip

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP325KCVF-20100-60	M20	100	60



Model: CP325KCVF-20150-100+positioning hole
 Surface Treatment: Nickel plated
 Material: Screw and chassis are all made of carbon steel
 Artwork: Screw and chassis are machined and connected by circlip

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP325KCVF-20150-100+positioning hole	M20	150	100



Model: CP325KCVF-20100-80
 Surface Treatment: Nickel plated
 Material: Screw and chassis are all made of carbon steel
 Artwork: The screw and chassis are machined, connected by circlip, and the screw head is milled with outer hexagon

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP325KCVF-20100-80	M20	100	80



Model: CP325KSVF-30100-80
 Surface Treatment: Nickel / Galvanized zinc
 Material: The screw and chassis are made of 304 stainless steel, the chassis is made of polyurethane, or all carbon steel
 Artwork: Screw and chassis are machined and connected with small screws

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP325KSVF-30100-80	M30	100	80



Model: CP325KCVF-16100-60
 Surface Treatment: Galvanized zinc
 Material: Screw and chassis are all made of carbon steel, chassis is added with polyurethane
 Artwork: Screw and chassis are machined and connected with small screws

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP325KCVF-16100-60	M16	100	60



Model: CP325KCF-1050-50
 Surface Treatment: Galvanized zinc
 Material: Screw and chassis are made of carbon steel
 Artwork: The screw is made of outer hexagon, fixed by nut and stamped by chassis

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP325KCF-1050-50	M10	50	50



Model: CP325KCVF-20100-100
 Surface Treatment: Electrophoretic painting
 Material: The screw and chassis are all made of carbon steel, the chassis is equipped with rubber pad
 Artwork: Screw and chassis are machined and connected by circlip

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP325KCVF-20100-100	M20	100	100

Specification:

Type: Steel Fixed Leveling Feet	Feet size: M10 / M16 / M20 / M30...
Surface Treatment: Nickel plated / galvanized / Chrome / blackened / painted, etc; 304 or 316 stainless steel is also available	
Material: Screw is made of carbon steel, chassis : rubber / reinforced nylon (PA6)	
Applicable Temperature: -60°C ~ 80°C	
Artwork: The screw and chassis are machined, connected by circlip, and the screw head is milled with outer hexagon	

Model No.: CP326
 Product name: Swivel Leveling Feet
 Feet size: M8 / M10 / M16 / M20 / M24...



Model: CP328KUF-20150-100
 Surface Treatment: Nickel plated
 Material: Reinforced nylon (PA6) is used as the chassis, carbon steel is used as the screw
 Artwork: The screw is machined, connected by ball head and molded by chassis

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP326KUF-20150-100	M20	150	100



Model: CP326KUF-1030-40
 Surface Treatment: Nickel plated
 Material: Reinforced nylon (PA6) is used as the chassis, carbon steel is used as the screw
 Artwork: The screw is machined, connected by ball head and molded by chassis

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP326KUF-1030-40	M10	30	40



Model: CP328KUF-16100-60
 Surface Treatment: Nickel plated
 Material: Reinforced nylon (PA6) is used as the chassis, carbon steel is used as the screw
 Artwork: The screw is machined, connected by ball head, molded from chassis, with handle

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP326KUF-16100-60	M16	100	60



Model: CP326KUF-24150-140
 Surface Treatment: Nickel plated
 Material: The chassis is made of reinforced nylon (PA6), the screw is made of 304 stainless steel or carbon steel
 Artwork: The screw is machined, connected by ball head and molded by chassis

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP326KUF-24150-140	M24	150	140



Model: CP326KUF-16100-110
 Surface Treatment: Nickel plated
 Material: Reinforced nylon (PA6) is used as the chassis, carbon steel is used as the screw
 Artwork: The screw is machined, connected by ball head and molded by chassis

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP326KUF-16100-110	M16	100	110



Model: CP326KUF-16150-140
 Surface Treatment: Nickel plated
 Material: The chassis is made of reinforced nylon (PA6), the screw is made of 304 stainless steel or carbon steel
 Artwork: The screw is machined, connected by ball head and molded by chassis

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP326KUF-16150-140	M16	150	140



Model: CP326KUF-830-40
 Surface Treatment: Nickel plated
 Material: Reinforced nylon (PA6) is used as the chassis, carbon steel is used as the screw
 Artwork: The screw is machined, connected by ball head and molded by chassis

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP326KUF-830-40	M8	30	40



Model: CP326KUF-20150-140
 Surface Treatment: Nickel plated
 Material: Reinforced nylon (PA6) is used as the chassis, carbon steel is used as the screw
 Artwork: The screw is machined, connected by ball head and molded by chassis

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP326KUF-20150-140	M20	150	140



Model: CP326KUF-20150-100
 Surface Treatment: Nickel plated
 Material: The screw and chassis are all made of carbon steel, the chassis is equipped with rubber pad
 Artwork: Screw and chassis are machined and connected by circlip

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP326KUF-20150-100	M20	150	100

Specification:

Type: Swivel Leveling Feet

Feet size: M8 / M10 / M16 / M20 / M24...

Surface Treatment: Nickel plated / galvanized / Chrome / blackened / painted, etc; 304 or 316 stainless steel is also available

Material: Screw is made of carbon steel, chassis : rubber / reinforced nylon (PA6)

Applicable Temperature: -60°C ~ 80°C

Artwork: The screw is machined, connected by ball head and molded by chassis

Model No.: CP327
 Product name: Steel Swivel Leveling Feet
 Feet size: M8 / M16 / M20 / M30...



Model: CP327KCUF-20100-100
 Surface Treatment: Nickel plated
 Material: Screw and chassis are all made of carbon steel
 Artwork: Screw and chassis are machined and connected by ball joint

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP327KCUF-20100-100	M20	100	100



Model: CP327KCUF-20100-120
 Surface Treatment: Chrome plated
 Material: Screw and chassis are all made of carbon steel
 Artwork: Screw and chassis are machined and connected by ball joint

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP327KCUF-20100-120	M20	100	120



Model: CP327KCUF-830-40
 Surface Treatment: Nickel plated
 Material: Screw and chassis are all made of carbon steel
 Artwork: Screw and chassis are machined and connected by ball joint

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP327KCUF-830-40	M8	30	40



Model: CP327KCUF-16100-60
 Surface Treatment: Nickel plated
 Material: Screw and chassis are all made of carbon steel, with rubber pad at the bottom
 Artwork: Screw and chassis are machined and connected by ball joint

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP327KCUF-16100-60	M16	100	60



Model: CP327KCUF-16150-80
 Surface Treatment: Nickel plated
 Material: Screw and chassis are all made of carbon steel
 Artwork: Screw and chassis are machined and connected by ball joint

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP327KCUF-16150-80	M16	150	80



Model: CP327KCUF-30150-100
 Surface Treatment: Nickel plated
 Material: Screw and chassis are all made of carbon steel, with rubber pad at the bottom
 Artwork: Screw and chassis are machined and connected by ball joint

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP327KCUF-30150-100	M30	150	100



Model: CP327KCUF-16185-60
 Surface Treatment: Nickel plated
 Material: Screw and chassis are all made of carbon steel, with rubber pad at the bottom
 Artwork: Screw and chassis are machined and connected by ball joint

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP327KCUF-16185-60	M16	185	60



Leveling Feet



Model:CP327KCUF-20200-150
 Surface Treatment: Nickel plated
 Material: Screw and chassis are all made of carbon steel, with rubber pad at the bottom
 Artwork: Screw and chassis are machined and connected by ball joint

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP327KCUF-20200-150	M20	200	150



Model:CP327KCUF-1680-80
 Surface Treatment: Galvanized zinc
 Material: Screw and chassis are all carbon steel material
 Artwork: Both screw and chassis are machined, internal thread, self-made screw

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP327KCUF-1680-80	M16	80	80



Model:CP327KCUF-16100-80
 Surface Treatment: Nickel plated
 Material: Screw and chassis are all made of carbon steel
 Artwork: Screw and chassis are machined and connected by ball joint

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP327KCUF-16100-80	M16	100	80

Specification:

Type: Steel Swivel Leveling Feet	Feet size: M8 / M16 / M20 / M30...
Surface Treatment: Nickel plated / galvanized / Chrome / blackened / painted, etc; 304 or 316 stainless steel is also available	
Material: Screw and chassis are all made of carbon steel	
Applicable Temperature: -60°C ~ 200°C	
Artwork: Screw and chassis are machined and connected by ball joint	



Model No.: CP328
 Product name: Steel Bolt Hole Leveling Feet
 Feet size: M20 / M25...



Model: CP328KNUF-1 / 10-100
 Surface Treatment: Color zinc plating
 Material: All carbon steel material
 Artwork: The thread part adopts internal thread type, which can be used with external and internal thread equipment

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP328KNUF-1 / 10-100	1 inch	NA	100



Model: CP328KNUF-M20-80
 Surface Treatment: Nickel plating
 Material: All carbon steel material
 Artwork: The thread part adopts internal thread type, which can be used with external and internal thread equipment

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP328KNUF-M20-80	M20	NA	80

Specification:

Type: Steel Bolt Hole Leveling Feet	Feet size: M20 / M25...
Surface Treatment: Nickel plated / galvanized / Chrome / blackened / painted, etc; 304 or 316 stainless steel is also available	
Material: All carbon steel	
Applicable Temperature: -60°C ~ 200°C	
Artwork: The thread part adopts internal thread type, which can be used with external and internal thread equipment	

Model No.: CP329
 Product name: Furniture Leveling Feet
 Feet size: M8 / M10...



Model: CP329KLF-1045-42
 Surface Treatment: Galvanized zinc
 Material: The chassis is made of White PP material, coated with nickel plated iron sheet; the screw is made of carbon steel
 Artwork: The product chassis is made of white plastic clad iron sheet and fixed by machine riveting



Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP329KLF-1045-42	M10	45	42



Model: CP329KLF-825-25
 Surface Treatment: Galvanized zinc
 Material: The chassis is made of White and black PP material, coated with nickel plated iron sheet; the screw is made of carbon steel
 Artwork: The product chassis is made of white plastic clad iron sheet and fixed by machine riveting

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP329KLF-825-25	M8	25	25



Model: CP329KLF-830-35
 Surface Treatment: Galvanized zinc
 Material: The chassis is made of black PP material, coated with nickel plated iron sheet; the screw is made of carbon steel
 Artwork: The product chassis is made of white plastic clad iron sheet and fixed by machine riveting

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP329KLF-830-35	M8	30	35



Model: CP329KLF-825-35
 Surface Treatment: Galvanized zinc
 Material: The chassis is made of white PP material, coated with nickel plated iron sheet; the screw is made of carbon steel
 Artwork: The product chassis is made of white plastic clad iron sheet and fixed by machine riveting

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP329KLF-825-35	M8	25	35



Model: CP329KLF-3 / 8*38-35(teeth in British system)
 Surface Treatment: Galvanized zinc
 Material: The chassis is made of white PP material, coated with nickel plated iron sheet; the screw is made of carbon steel
 Artwork: The product chassis is made of white plastic clad iron sheet and fixed by machine riveting

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP329KLF-3 / 8*38-35	M8	38	35



Model: CP329KLF-825-38
 Surface Treatment: Galvanized zinc
 Material: The chassis is made of reinforced nylon, screw carbon steel
 Artwork: The product screw is made of cold beating, and the chassis is made of injection molding

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP329KLF-825-38	M8	25	38

Specification:

Type: Furniture Leveling Feet	Feet size: M8 / M10...
Surface Treatment: Galvanized, (nickel / chromium / blackening / painting are also optional)	
Material: The chassis is made of White PP material or nylon, coated with nickel plated iron sheet; the screw is made of carbon steel	
Applicable Temperature: -60°C ~ 70°C	
Artwork: The product screw is made of cold beating or PP material, and the chassis is made of injection molding	



Leveling Feet

Model No.: CP330

Product name: Rubber Leveling Feet

Feet size: M8 / M12 / M16...



Model: CP330KSF-1260-50

Surface Treatment: Galvanized zinc or nickel plated

Material: Rubber pad at the bottom, carbon steel for screw and bottom shell

Artwork: The screw adopts the outer hexagon, the nut is fixed, and the bottom is made of iron clad thick rubber

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP330KSF-1260-50	M12	60	50



Model: CP330KSF-830-40

Surface Treatment: Galvanized zinc

Material: Rubber pad at the bottom, carbon steel for screw and bottom shell

Artwork: The screw adopts the outer hexagon, the nut is fixed, and the bottom is made of iron clad thick rubber

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP330KSF-830-40	M8	30	40



Model: CP330KSF-1650-60

Surface Treatment: Galvanized zinc

Material: Rubber pad at the bottom, carbon steel for screw and bottom shell

Artwork: The screw adopts the outer hexagon, the nut is fixed, and the bottom is made of iron clad thick rubber

Model	Feet size	Tread Stem Length(mm)	Chassis diameter(mm)
CP330KSF-1650-60	M16	60	60



Model: CP330KNF-39 / 49

Surface Treatment: NA

Material: Black Nylon

Artwork: made of nylon injection molding

Model	Outer diameter 1(mm)	Outer diameter 2(mm)	Round pipe size1 (mm)	Round pipe size2 (mm)
CP330KNF-39 / 49	38	49	40	50

Specification:

Type: Rubber Leveling Feet

Feet size: M8 / M12 / M16...

Surface Treatment: Galvanized zinc / nickel / chromium / blackening / painting etc

Material: Rubber pad at the bottom, carbon steel for screw and bottom shell

Applicable Temperature: -60°C ~ 70°C

Artwork: The screw is made of outer hexagon or machined, connected by circlip, fixed by nut, and the bottom is made of iron clad thick rubber